
Factory Boy Documentation

Release 0.1.0

Raphaël Barrois, Mark Sandstrom

Feb 04, 2020

Contents

1	Links	3
2	Download	5
3	Usage	7
3.1	Defining factories	7
3.2	ORM integration	8
3.3	Using factories	8
3.4	Realistic, random values	8
3.5	Reproducible random values	9
3.6	Lazy Attributes	9
3.7	Sequences	10
3.8	Associations	10
4	Support Policy	11
5	Debugging factory_boy	13
6	Contributing	15
7	Contents, indices and tables	17
7.1	Introduction	17
7.2	Reference	22
7.3	Using factory_boy with ORMs	51
7.4	Common recipes	58
7.5	Fuzzy attributes	68
7.6	Examples	73
7.7	Internals	75
7.8	ChangeLog	77
7.9	Credits	88
7.10	Ideas	91
	Python Module Index	93
	Index	95

factory_boy is a fixtures replacement based on thoughtbot's `factory_bot`.

As a fixtures replacement tool, it aims to replace static, hard to maintain fixtures with easy-to-use factories for complex objects.

Instead of building an exhaustive test setup with every possible combination of corner cases, `factory_boy` allows you to use objects customized for the current test, while only declaring the test-specific fields:

```
class FooTests(unittest.TestCase):

    def test_with_factory_boy(self):
        # We need a 200€, paid order, shipping to australia, for a VIP customer
        order = OrderFactory(
            amount=200,
            status='PAID',
            customer__is_vip=True,
            address__country='AU',
        )
        # Run the tests here

    def test_without_factory_boy(self):
        address = Address(
            street="42 fubar street",
            zipcode="42Z42",
            city="Sydney",
            country="AU",
        )
        customer = Customer(
            first_name="John",
            last_name="Doe",
            phone="+1234",
            email="john.doe@example.org",
            active=True,
            is_vip=True,
            address=address,
        )
        # etc.
```

factory_boy is designed to work well with various ORMs (Django, Mongo, SQLAlchemy), and can easily be extended for other libraries.

Its main features include:

- Straightforward declarative syntax
- Chaining factory calls while retaining the global context
- Support for multiple build strategies (saved/unsaved instances, stubbed objects)
- Multiple factories per class support, including inheritance

CHAPTER 1

Links

- Documentation: <https://factoryboy.readthedocs.io/>
- Repository: https://github.com/FactoryBoy/factory_boy
- Package: https://pypi.org/project/factory_boy/
- Mailing-list: factoryboy@googlegroups.com | <https://groups.google.com/forum/#!forum/factoryboy>

CHAPTER 2

Download

PyPI: https://pypi.org/project/factory_boy/

```
$ pip install factory_boy
```

Source: https://github.com/FactoryBoy/factory_boy/

```
$ git clone git://github.com/FactoryBoy/factory_boy/  
$ python setup.py install
```

Note: This section provides a quick summary of `factory_boy` features. A more detailed listing is available in the full documentation.

3.1 Defining factories

Factories declare a set of attributes used to instantiate a Python object. The class of the object must be defined in the `model` field of a `class Meta:` attribute:

```
import factory
from . import models

class UserFactory(factory.Factory):
    class Meta:
        model = models.User

    first_name = 'John'
    last_name = 'Doe'
    admin = False

# Another, different, factory for the same object
class AdminFactory(factory.Factory):
    class Meta:
        model = models.User

    first_name = 'Admin'
    last_name = 'User'
    admin = True
```

3.2 ORM integration

factory_boy integration with Object Relational Mapping (ORM) tools is provided through specific factory. Factory subclasses:

- Django, with `factory.django.DjangoModelFactory`
- Mogo, with `factory.mogo.MogoFactory`
- MongoEngine, with `factory.mongoengine.MongoEngineFactory`
- SQLAlchemy, with `factory.alchemy.SQLAlchemyModelFactory`

More details can be found in the *ORM section*.

3.3 Using factories

factory_boy supports several different build strategies: build, create, and stub:

```
# Returns a User instance that's not saved
user = UserFactory.build()

# Returns a saved User instance.
# UserFactory must subclass an ORM base class, such as DjangoModelFactory.
user = UserFactory.create()

# Returns a stub object (just a bunch of attributes)
obj = UserFactory.stub()
```

You can use the Factory class as a shortcut for the default build strategy:

```
# Same as UserFactory.create()
user = UserFactory()
```

No matter which strategy is used, it's possible to override the defined attributes by passing keyword arguments:

```
# Build a User instance and override first_name
>>> user = UserFactory.build(first_name='Joe')
>>> user.first_name
"Joe"
```

It is also possible to create a bunch of objects in a single call:

```
>>> users = UserFactory.build_batch(10, first_name="Joe")
>>> len(users)
10
>>> [user.first_name for user in users]
["Joe", "Joe", "Joe", "Joe", "Joe", "Joe", "Joe", "Joe", "Joe", "Joe"]
```

3.4 Realistic, random values

Demos look better with random yet realistic values; and those realistic values can also help discover bugs. For this, factory_boy relies on the excellent [faker](#) library:

```
class RandomUserFactory(factory.Factory):
    class Meta:
        model = models.User

        first_name = factory.Faker('first_name')
        last_name = factory.Faker('last_name')
```

```
>>> UserFactory()
<User: Lucy Murray>
```

3.5 Reproducible random values

The use of fully randomized data in tests is quickly a problem for reproducing broken builds. To that purpose, `factory_boy` provides helpers to handle the random seeds it uses, located in the `factory.random` module:

```
import factory.random

def setup_test_environment():
    factory.random.reseed_random('my_awesome_project')
    # Other setup here
```

3.6 Lazy Attributes

Most factory attributes can be added using static values that are evaluated when the factory is defined, but some attributes (such as fields whose value is computed from other elements) will need values assigned each time an instance is generated.

These “lazy” attributes can be added as follows:

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

        first_name = 'Joe'
        last_name = 'Blow'
        email = factory.LazyAttribute(lambda a: '{0}.{1}@example.com'.format(a.first_name,
↪ a.last_name).lower())
        date_joined = factory.LazyFunction(datetime.now)
```

```
>>> UserFactory().email
"joe.blow@example.com"
```

Note: `LazyAttribute` calls the function with the object being constructed as an argument, when `LazyFunction` does not send any argument.

3.7 Sequences

Unique values in a specific format (for example, e-mail addresses) can be generated using sequences. Sequences are defined by using `Sequence` or the decorator `sequence`:

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

        email = factory.Sequence(lambda n: 'person{0}@example.com'.format(n))

>>> UserFactory().email
'person0@example.com'
>>> UserFactory().email
'person1@example.com'
```

3.8 Associations

Some objects have a complex field, that should itself be defined from a dedicated factories. This is handled by the `SubFactory` helper:

```
class PostFactory(factory.Factory):
    class Meta:
        model = models.Post

        author = factory.SubFactory(UserFactory)
```

The associated object's strategy will be used:

```
# Builds and saves a User and a Post
>>> post = PostFactory()
>>> post.id is None # Post has been 'saved'
False
>>> post.author.id is None # post.author has been saved
False

# Builds but does not save a User, and then builds but does not save a Post
>>> post = PostFactory.build()
>>> post.id is None
True
>>> post.author.id is None
True
```

CHAPTER 4

Support Policy

`factory_boy` supports Python 2.7, 3.5 to 3.8, as well as PyPy 2.7 and 5.8.

- **Django's** [supported versions](<https://www.djangoproject.com/download/#supported-versions>).
- **SQLAlchemy**: [latest version on PyPI](<https://pypi.org/project/SQLAlchemy/>).
- **mongoengine**: [latest version on PyPI](<https://pypi.org/project/mongoengine/>).

Debugging factory_boy

Debugging `factory_boy` can be rather complex due to the long chains of calls. Detailed logging is available through the `factory` logger.

A helper, `factory.debug()`, is available to ease debugging:

```
with factory.debug():
    obj = TestModel2Factory()

import logging
logger = logging.getLogger('factory')
logger.addHandler(logging.StreamHandler())
logger.setLevel(logging.DEBUG)
```

This will yield messages similar to those (artificial indentation):

```
BaseFactory: Preparing tests.test_using.TestModel2Factory(extra={})
  LazyStub: Computing values for tests.test_using.TestModel2Factory(two=
↳<OrderedDeclarationWrapper for <factory.declarations.SubFactory object at 0x1e15610>
↳>)
    SubFactory: Instantiating tests.test_using.TestModelFactory(__containers=(
↳<LazyStub for tests.test_using.TestModel2Factory>,), one=4), create=True
      BaseFactory: Preparing tests.test_using.TestModelFactory(extra={'__containers': (
↳<LazyStub for tests.test_using.TestModel2Factory>,), 'one': 4})
        LazyStub: Computing values for tests.test_using.TestModelFactory(one=4)
          LazyStub: Computed values, got tests.test_using.TestModelFactory(one=4)
        BaseFactory: Generating tests.test_using.TestModelFactory(one=4)
          LazyStub: Computed values, got tests.test_using.TestModel2Factory(two=<tests.test_
↳using.TestModel object at 0x1e15410>)
        BaseFactory: Generating tests.test_using.TestModel2Factory(two=<tests.test_using.
↳TestModel object at 0x1e15410>)
```


CHAPTER 6

Contributing

factory_boy is distributed under the MIT License.

Issues should be opened through [GitHub Issues](#); whenever possible, a pull request should be included. Questions and suggestions are welcome on the [mailing-list](#).

All pull request should pass the test suite, which can be launched simply with:

```
$ make test
```

In order to test coverage, please use:

```
$ make coverage
```

To test with a specific framework version, you may use a `tox` target:

```
# list all tox environments
$ tox --listenvs

# run tests inside a specific environment
$ tox -e py36-django20-alchemy13-mongoengine017
```

Valid options are:

- DJANGO for Django
- MONGOENGINE for mongoengine
- ALCHEMY for SQLAlchemy

To avoid running mongoengine tests (e.g no mongo server installed), run:

```
$ make SKIP_MONGOENGINE=1 test
```


7.1 Introduction

The purpose of `factory_boy` is to provide a default way of getting a new instance, while still being able to override some fields on a per-call basis.

Note: This section will drive you through an overview of `factory_boy`'s feature. New users are advised to spend a few minutes browsing through this list of useful helpers.

Users looking for quick helpers may take a look at *Common recipes*, while those needing detailed documentation will be interested in the *Reference* section.

7.1.1 Basic usage

Factories declare a set of attributes used to instantiate an object, whose class is defined in the `class Meta`'s `model` attribute:

- Subclass `factory.Factory` (or a more suitable subclass)
- Add a `class Meta: block`
- Set its `model` attribute to the target class
- Add defaults for keyword args to pass to the associated class' `__init__` method

```
import factory
from . import base

class UserFactory(factory.Factory):
    class Meta:
        model = base.User
```

(continues on next page)

(continued from previous page)

```
firstname = "John"
lastname = "Doe"
```

You may now get `base.User` instances trivially:

```
>>> john = UserFactory()
<User: John Doe>
```

It is also possible to override the defined attributes by passing keyword arguments to the factory:

```
>>> jack = UserFactory(firstname="Jack")
<User: Jack Doe>
```

A given class may be associated to many *Factory* subclasses:

```
class EnglishUserFactory(factory.Factory):
    class Meta:
        model = base.User

        firstname = "John"
        lastname = "Doe"
        lang = 'en'

class FrenchUserFactory(factory.Factory):
    class Meta:
        model = base.User

        firstname = "Jean"
        lastname = "Dupont"
        lang = 'fr'
```

```
>>> EnglishUserFactory()
<User: John Doe (en)>
>>> FrenchUserFactory()
<User: Jean Dupont (fr)>
```

7.1.2 Sequences

When a field has a unique key, each object generated by the factory should have a different value for that field. This is achieved with the *Sequence* declaration:

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

        username = factory.Sequence(lambda n: 'user%d' % n)
```

```
>>> UserFactory()
<User: user0>
>>> UserFactory()
<User: user1>
```

Note: For more complex situations, you may also use the `@sequence()` decorator (note that `self` is not added as first parameter):

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

    @factory.sequence
    def username(n):
        return 'user%d' % n
```

7.1.3 LazyFunction

In simple cases, calling a function is enough to compute the value. If that function doesn't depend on the object being built, use `LazyFunction` to call that function; it should receive a function taking no argument and returning the value for the field:

```
class LogFactory(factory.Factory):
    class Meta:
        model = models.Log

    timestamp = factory.LazyFunction(datetime.now)
```

```
>>> LogFactory()
<Log: log at 2016-02-12 17:02:34>

>>> # The LazyFunction can be overridden
>>> LogFactory(timestamp=now - timedelta(days=1))
<Log: log at 2016-02-11 17:02:34>
```

Note: For complex cases when you happen to write a specific function, the `@lazy_attribute()` decorator should be more appropriate.

7.1.4 LazyAttribute

Some fields may be deduced from others, for instance the email based on the username. The `LazyAttribute` handles such cases: it should receive a function taking the object being built and returning the value for the field:

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

    username = factory.Sequence(lambda n: 'user%d' % n)
    email = factory.LazyAttribute(lambda obj: '%s@example.com' % obj.username)
```

```
>>> UserFactory()
<User: user1 (user1@example.com)>

>>> # The LazyAttribute handles overridden fields
```

(continues on next page)

(continued from previous page)

```
>>> UserFactory(username='john')
<User: john (john@example.com)>

>>> # They can be directly overridden as well
>>> UserFactory(email='doe@example.com')
<User: user3 (doe@example.com)>
```

Note: As for *Sequence*, a `@lazy_attribute()` decorator is available:

```
class UserFactory(factory.Factory):
    class Meta:
        model = models.User

    username = factory.Sequence(lambda n: 'user%d' % n)

    @factory.lazy_attribute
    def email(self):
        return '%s@example.com' % self.username
```

7.1.5 Inheritance

Once a “base” factory has been defined for a given class, alternate versions can be easily defined through subclassing. The subclassed *Factory* will inherit all declarations from its parent, and update them with its own declarations:

```
class UserFactory(factory.Factory):
    class Meta:
        model = base.User

    firstname = "John"
    lastname = "Doe"
    group = 'users'

class AdminFactory(UserFactory):
    admin = True
    group = 'admins'
```

```
>>> user = UserFactory()
>>> user
<User: John Doe>
>>> user.group
'users'

>>> admin = AdminFactory()
>>> admin
<User: John Doe (admin)>
>>> admin.group # The AdminFactory field has overridden the base field
'admins'
```

Any argument of all factories in the chain can easily be overridden:

```
>>> super_admin = AdminFactory(group='superadmins', lastname="Lennon")
>>> super_admin
```

(continues on next page)

(continued from previous page)

```
<User: John Lennon (admin)>
>>> super_admin.group # Overridden at call time
'superadmins'
```

7.1.6 Non-kwarg arguments

Some classes take a few, non-kwarg arguments first.

This is handled by the `inline_args` attribute:

```
class MyFactory(factory.Factory):
    class Meta:
        model = MyClass
        inline_args = ('x', 'y')

    x = 1
    y = 2
    z = 3
```

```
>>> MyFactory(y=4)
<MyClass(1, 4, z=3)>
```

7.1.7 Altering a factory's behaviour: parameters and traits

Some classes are better described with a few, simple parameters, that aren't fields on the actual model. In that case, use a `Params` declaration:

```
class RentalFactory(factory.Factory):
    class Meta:
        model = Rental

    begin = factory.fuzzy.FuzzyDate(start_date=datetime.date(2000, 1, 1))
    end = factory.LazyAttribute(lambda o: o.begin + o.duration)

    class Params:
        duration = 12
```

```
>>> RentalFactory(duration=0)
<Rental: 2012-03-03 -> 2012-03-03>
>>> RentalFactory(duration=10)
<Rental: 2008-12-16 -> 2012-12-26>
```

When many fields should be updated based on a flag, use `Traits` instead:

```
class OrderFactory(factory.Factory):
    status = 'pending'
    shipped_by = None
    shipped_on = None

    class Meta:
        model = Order

    class Params:
```

(continues on next page)

(continued from previous page)

```
shipped = factory.Trait(  
    status='shipped',  
    shipped_by=factory.SubFactory(EmployeeFactory),  
    shipped_on=factory.LazyFunction(datetime.date.today),  
)
```

A trait is toggled by a single boolean value:

```
>>> OrderFactory()  
<Order: pending>  
>>> OrderFactory(shipped=True)  
<Order: shipped by John Doe on 2016-04-02>
```

7.1.8 Strategies

All factories support two built-in strategies:

- `build` provides a local object
- `create` instantiates a local object, and saves it to the database.

Note: For 1.X versions, the `create` will actually call `AssociatedClass.objects.create`, as for a Django model.

Starting from 2.0, `factory.Factory.create()` simply calls `AssociatedClass(**kwargs)`. You should use `DjangoModelFactory` for Django models.

When a *Factory* includes related fields (*SubFactory*, *RelatedFactory*), the parent's strategy will be pushed onto related factories.

Calling a *Factory* subclass will provide an object through the default strategy:

```
class MyFactory(factory.Factory):  
    class Meta:  
        model = MyClass
```

```
>>> MyFactory.create()  
<MyFactory: X (saved)>  
  
>>> MyFactory.build()  
<MyFactory: X (unsaved)>  
  
>>> MyFactory() # equivalent to MyFactory.create()  
<MyClass: X (saved)>
```

The default strategy can be changed by setting the class `Meta` *strategy* attribute.

7.2 Reference

This section offers an in-depth description of `factory_boy` features.

For internals and customization points, please refer to the *Internals* section.

7.2.1 The `Factory` class

Meta options

`class factory.FactoryOptions`

New in version 2.4.0.

A *Factory*'s behaviour can be tuned through a few settings.

For convenience, they are declared in a single class `Meta` attribute:

```
class MyFactory(factory.Factory):
    class Meta:
        model = MyObject
        abstract = False
```

`model`

This optional attribute describes the class of objects to generate.

If unset, it will be inherited from parent *Factory* subclasses.

New in version 2.4.0.

`get_model_class()`

Returns the actual model class (*FactoryOptions.model* might be the path to the class; this function will always return a proper class).

`abstract`

This attribute indicates that the *Factory* subclass should not be used to generate objects, but instead provides some extra defaults.

It will be automatically set to `True` if neither the *Factory* subclass nor its parents define the *model* attribute.

Warning: This flag is reset to `False` when a *Factory* subclasses another one if a *model* is set.

New in version 2.4.0.

`inline_args`

Some factories require non-keyword arguments to their `__init__()`. They should be listed, in order, in the *inline_args* attribute:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User
        inline_args = ('login', 'email')

    login = 'john'
    email = factory.LazyAttribute(lambda o: '%s@example.com' % o.login)
    firstname = "John"
```

```
>>> UserFactory()
<User: john>
>>> User('john', 'john@example.com', firstname="John") # actual call
```

New in version 2.4.0.

exclude

While writing a *Factory* for some object, it may be useful to have general fields helping defining others, but that should not be passed to the model class; for instance, a field named 'now' that would hold a reference time used by other objects.

Factory fields whose name are listed in *exclude* will be removed from the set of args/kwargs passed to the underlying class; they can be any valid factory_boy declaration:

```
class OrderFactory(factory.Factory):
    class Meta:
        model = Order
        exclude = ('now',)

    now = factory.LazyFunction(datetime.datetime.utcnow)
    started_at = factory.LazyAttribute(lambda o: o.now - datetime.
↳timedelta(hours=1))
    paid_at = factory.LazyAttribute(lambda o: o.now - datetime.
↳timedelta(minutes=50))
```

```
>>> OrderFactory()    # The value of 'now' isn't passed to Order()
<Order: started 2013-04-01 12:00:00, paid 2013-04-01 12:10:00>

>>> # An alternate value may be passed for 'now'
>>> OrderFactory(now=datetime.datetime(2013, 4, 1, 10))
<Order: started 2013-04-01 09:00:00, paid 2013-04-01 09:10:00>
```

New in version 2.4.0.

rename

Sometimes, a model expects a field with a name already used by one of *Factory*'s methods.

In this case, the *rename* attributes allows to define renaming rules: the keys of the *rename* dict are those used in the *Factory* declarations, and their values the new name:

```
class ImageFactory(factory.Factory):
    # The model expects "attributes"
    form_attributes = ['thumbnail', 'black-and-white']

    class Meta:
        model = Image
        rename = {'form_attributes': 'attributes'}
```

strategy

Use this attribute to change the strategy used by a *Factory*. The default is *CREATE_STRATEGY*.

Attributes and methods

class factory.Factory

Class-level attributes:

Meta

_meta

New in version 2.4.0.

The *FactoryOptions* instance attached to a *Factory* class is available as a *_meta* attribute.

Params

New in version 2.7.0.

The extra parameters attached to a *Factory* are declared through a *Params* class. See the “Parameters” section for more information.

`_options_class`

New in version 2.4.0.

If a *Factory* subclass needs to define additional, extra options, it has to provide a custom *FactoryOptions* subclass.

A pointer to that custom class should be provided as `_options_class` so that the *Factory*-building metaclass can use it instead.

Base functions:

The *Factory* class provides a few methods for getting objects; the usual way being to simply call the class:

```
>>> UserFactory() # Calls UserFactory.create()
>>> UserFactory(login='john') # Calls UserFactory.create(login='john')
```

Under the hood, `factory_boy` will define the *Factory* `__new__()` method to call the default *strategy* of the *Factory*.

A specific strategy for getting instance can be selected by calling the adequate method:

classmethod `build` (*cls*, ***kwargs*)

Provides a new object, using the ‘build’ strategy.

classmethod `build_batch` (*cls*, *size*, ***kwargs*)

Provides a list of *size* instances from the *Factory*, through the ‘build’ strategy.

classmethod `create` (*cls*, ***kwargs*)

Provides a new object, using the ‘create’ strategy.

classmethod `create_batch` (*cls*, *size*, ***kwargs*)

Provides a list of *size* instances from the *Factory*, through the ‘create’ strategy.

classmethod `stub` (*cls*, ***kwargs*)

Provides a new stub

classmethod `stub_batch` (*cls*, *size*, ***kwargs*)

Provides a list of *size* stubs from the *Factory*.

classmethod `generate` (*cls*, *strategy*, ***kwargs*)

Provide a new instance, with the provided *strategy*.

classmethod `generate_batch` (*cls*, *strategy*, *size*, ***kwargs*)

Provides a list of *size* instances using the specified *strategy*.

classmethod `simple_generate` (*cls*, *create*, ***kwargs*)

Provide a new instance, either built (*create*=False) or created (*create*=True).

classmethod `simple_generate_batch` (*cls*, *create*, *size*, ***kwargs*)

Provides a list of *size* instances, either built or created according to *create*.

Extension points:

A *Factory* subclass may override a couple of class methods to adapt its behaviour:

classmethod `_adjust_kwargs` (*cls*, ***kwargs*)

The `_adjust_kwargs()` extension point allows for late fields tuning.

It is called once keyword arguments have been resolved and post-generation items removed, but before the `inline_args` extraction phase.

```
class UserFactory(factory.Factory):

    @classmethod
    def _adjust_kwargs(cls, **kwargs):
        # Ensure ``lastname`` is upper-case.
        kwargs['lastname'] = kwargs['lastname'].upper()
        return kwargs
```

classmethod `_setup_next_sequence` (*cls*)

This method will compute the first value to use for the sequence counter of this factory.

It is called when the first instance of the factory (or one of its subclasses) is created.

Subclasses may fetch the next free ID from the database, for instance.

classmethod `_build` (*cls*, *model_class*, **args*, ***kwargs*)

This class method is called whenever a new instance needs to be built. It receives the model class (provided to *model*), and the positional and keyword arguments to use for the class once all has been computed.

Subclasses may override this for custom APIs.

classmethod `_create` (*cls*, *model_class*, **args*, ***kwargs*)

The `_create()` method is called whenever an instance needs to be created. It receives the same arguments as `_build()`.

Subclasses may override this for specific persistence backends:

```
class BaseBackendFactory(factory.Factory):
    class Meta:
        abstract = True # Optional

    @classmethod
    def _create(cls, model_class, *args, **kwargs):
        obj = model_class(*args, **kwargs)
        obj.save()
        return obj
```

classmethod `_after_postgeneration` (*cls*, *obj*, *create*, *results=None*)

Parameters

- **obj** (*object*) – The object just generated
- **create** (*bool*) – Whether the object was ‘built’ or ‘created’
- **results** (*dict*) – Map of post-generation declaration name to call result

The `_after_postgeneration()` is called once post-generation declarations have been handled.

Its arguments allow to handle specifically some post-generation return values, for instance.

Advanced functions:

classmethod `reset_sequence` (*cls*, *value=None*, *force=False*)

Parameters

- **value** (*int*) – The value to reset the sequence to
- **force** (*bool*) – Whether to force-reset the sequence

Allows to reset the sequence counter for a *Factory*. The new value can be passed in as the *value* argument:

```
>>> SomeFactory.build().sequenced_attribute
0
>>> SomeFactory.reset_sequence(4)
>>> SomeFactory.build().sequenced_attribute
4
```

Since subclasses of a non-*abstract Factory* share the same sequence counter, special care needs to be taken when resetting the counter of such a subclass.

By default, `reset_sequence()` will raise a `ValueError` when called on a subclassed *Factory* subclass. This can be avoided by passing in the `force=True` flag:

```
>>> InheritedFactory.reset_sequence()
Traceback (most recent call last):
  File "factory_boy/tests/test_base.py", line 179, in test_reset_sequence_
↳ subclass_parent
    SubTestObjectFactory.reset_sequence()
  File "factory_boy/factory/base.py", line 250, in reset_sequence
    "Cannot reset the sequence of a factory subclass. "
ValueError: Cannot reset the sequence of a factory subclass. Please call_
↳ reset_sequence() on the root factory, or call reset_sequence(forward=True).

>>> InheritedFactory.reset_sequence(force=True)
>>>
```

This is equivalent to calling `reset_sequence()` on the base factory in the chain.

Parameters

New in version 2.7.0.

Some models have many fields that can be summarized by a few parameters; for instance, a train with many cars — each complete with serial number, manufacturer, ...; or an order that can be pending/shipped/received, with a few fields to describe each step.

When building instances of such models, a couple of parameters can be enough to determine all other fields; this is handled by the *Params* section of a *Factory* declaration.

Simple parameters

Some factories only need little data:

```
class ConferenceFactory(factory.Factory):
    class Meta:
        model = Conference

    class Params:
        duration = 'short' # Or 'long'

    start_date = factory.fuzzy.FuzzyDate()
    end_date = factory.LazyAttribute(
        lambda o: o.start_date + datetime.timedelta(days=2 if o.duration == 'short'
↳ else 7)
    )
    sprints_start = factory.LazyAttribute(
```

(continues on next page)

(continued from previous page)

```

        lambda o: o.end_date - datetime.timedelta(days=0 if o.duration == 'short'
↪else 1)
    )

```

```

>>> ConferenceFactory(duration='short')
<Conference: DUTH 2015 (2015-11-05 - 2015-11-08, sprints 2015-11-08)>
>>> ConferenceFactory(duration='long')
<Conference: DjangoConEU 2016 (2016-03-30 - 2016-04-03, sprints 2016-04-02)>

```

Any simple parameter provided to the *Factory.Params* section is available to the whole factory, but not passed to the final class (similar to the *exclude* behavior).

Traits

class `factory.Trait` (***kwargs*)
 New in version 2.7.0.

A trait's parameters are the fields it should alter when enabled.

For more complex situations, it is helpful to override a few fields at once:

```

class OrderFactory(factory.Factory):
    class Meta:
        model = Order

    state = 'pending'
    shipped_on = None
    shipped_by = None

    class Params:
        shipped = factory.Trait(
            state='shipped',
            shipped_on=datetime.date.today(),
            shipped_by=factory.SubFactory(EmployeeFactory),
        )

```

Such a *Trait* is activated or disabled by a single boolean field:

```

>>> OrderFactory()
<Order: pending>
Order(state='pending')
>>> OrderFactory(shipped=True)
<Order: shipped by John Doe on 2016-04-02>

```

A *Trait* can be enabled/disabled by a *Factory* subclass:

```

class ShippedOrderFactory(OrderFactory):
    shipped = True

```

Values set in a *Trait* can be overridden by call-time values:

```

>>> OrderFactory(shipped=True, shipped_on=last_year)
<Order: shipped by John Doe on 2015-04-20>

```

Traits can be chained:


```

class OrderFactory(factory.Factory):
    class Meta:
        model = Order

    # Can be pending/shipping/received
    state = 'pending'
    shipped_on = None
    shipped_by = None
    received_on = None
    received_by = None

    class Params:
        shipped = factory.Trait(
            state='shipped',
            shipped_on=datetime.date.today,
            shipped_by=factory.SubFactory(EmployeeFactory),
        )
        received = factory.Trait(
            shipped=True,
            state='received',
            shipped_on=datetime.date.today - datetime.timedelta(days=4),
            received_on=datetime.date.today,
            received_by=factory.SubFactory(CustomerFactory),
        )

```

```

>>> OrderFactory(received=True)
<Order: shipped by John Doe on 2016-03-20, received by Joan Smith on 2016-04-02>

```

A *Trait* might be overridden in *Factory* subclasses:

```

class LocalOrderFactory(OrderFactory):

    class Params:
        received = factory.Trait(
            shipped=True,
            state='received',
            shipped_on=datetime.date.today - datetime.timedelta(days=1),
            received_on=datetime.date.today,
            received_by=factory.SubFactory(CustomerFactory),
        )

```

```

>>> LocalOrderFactory(received=True)
<Order: shipped by John Doe on 2016-04-01, received by Joan Smith on 2016-04-02>

```

Note: When overriding a *Trait*, the whole declaration **MUST** be replaced.

Strategies

factory_boy supports two main strategies for generating instances, plus stubs.

factory.BUILD_STRATEGY

The 'build' strategy is used when an instance should be created, but not persisted to any datastore.

It is usually a simple call to the `__init__()` method of the *model* class.

factory.CREATE_STRATEGY

The 'create' strategy builds and saves an instance into its appropriate datastore.

This is the default strategy of factory_boy; it would typically instantiate an object, then save it:

```
>>> obj = self._associated_class(*args, **kwargs)
>>> obj.save()
>>> return obj
```

Warning: For backward compatibility reasons, the default behaviour of factory_boy is to call `MyClass.objects.create(*args, **kwargs)` when using the create strategy.

That policy will be used if the *associated class* has an `objects` attribute *and* the `_create()` classmethod of the *Factory* wasn't overridden.

factory.use_strategy(strategy)

Decorator

Change the default strategy of the decorated *Factory* to the chosen *strategy*:

```
@use_strategy(factory.BUILD_STRATEGY)
class UserBuildingFactory(UserFactory):
    pass
```

factory.STUB_STRATEGY

The 'stub' strategy is an exception in the factory_boy world: it doesn't return an instance of the *model* class, and actually doesn't require one to be present.

Instead, it returns an instance of *StubObject* whose attributes have been set according to the declarations.

class factory.StubObject(object)

A plain, stupid object. No method, no helpers, simply a bunch of attributes.

It is typically instantiated, then has its attributes set:

```
>>> obj = StubObject()
>>> obj.x = 1
>>> obj.y = 2
```

class factory.StubFactory(Factory)

An *abstract Factory*, with a default strategy set to *STUB_STRATEGY*.

factory.debug(logger='factory', stream=None)

Parameters

- **logger** (*str*) – The name of the logger to enable debug for
- **stream** (*file*) – The stream to send debug output to, defaults to `sys.stderr`

Context manager to help debugging factory_boy behavior. It will temporarily put the target logger (e.g 'factory') in debug mode, sending all output to `:obj~-sys.stderr`; upon leaving the context, the logging levels are reset.

A typical use case is to understand what happens during a single factory call:

```
with factory.debug():
    obj = TestModel2Factory()
```

This will yield messages similar to those (artificial indentation):

```

BaseFactory: Preparing tests.test_using.TestModel2Factory (extra={})
  LazyStub: Computing values for tests.test_using.TestModel2Factory (two=
↳<OrderedDeclarationWrapper for <factory.declarations.SubFactory object at 0x1e15610>>)
    SubFactory: Instantiating tests.test_using.TestModelFactory (__containers=(
↳<LazyStub for tests.test_using.TestModel2Factory>,), one=4), create=True
      BaseFactory: Preparing tests.test_using.TestModelFactory (extra={'__containers
↳': (<LazyStub for tests.test_using.TestModel2Factory>,), 'one': 4})
        LazyStub: Computing values for tests.test_using.TestModelFactory (one=4)
        LazyStub: Computed values, got tests.test_using.TestModelFactory (one=4)
        BaseFactory: Generating tests.test_using.TestModelFactory (one=4)
        LazyStub: Computed values, got tests.test_using.TestModel2Factory (two=<tests.
↳test_using.TestModel object at 0x1e15410>)
      BaseFactory: Generating tests.test_using.TestModel2Factory (two=<tests.test_using.
↳TestModel object at 0x1e15410>)

```

7.2.2 Declarations

Faker

class `factory.Faker` (*provider, locale=None, **kwargs*)

In order to easily define realistic-looking factories, use the *Faker* attribute declaration.

This is a wrapper around *faker*; its argument is the name of a faker provider:

```

class UserFactory(factory.Factory):
    class Meta:
        model = User

    name = factory.Faker('name')

```

```

>>> user = UserFactory()
>>> user.name
'Lucy Cechtelar'

```

locale

If a custom locale is required for one specific field, use the *locale* parameter:

```

class UserFactory(factory.Factory):
    class Meta:
        model = User

    name = factory.Faker('name', locale='fr_FR')

```

```

>>> user = UserFactory()
>>> user.name
'Jean Valjean'

```

classmethod `override_default_locale` (*cls, locale*)

If the locale needs to be overridden for a whole test, use *override_default_locale()*:

```

>>> with factory.Faker.override_default_locale('de_DE'):
...     UserFactory()
<User: Johannes Brahms>

```

classmethod `add_provider` (*cls, locale=None*)

Some projects may need to fake fields beyond those provided by `faker`; in such cases, use `factory.Faker.add_provider()` to declare additional providers for those fields:

```
factory.Faker.add_provider(SmileProvider)

class FaceFactory(factory.Factory):
    class Meta:
        model = Face

    smiley = factory.Faker('smiley')
```

LazyFunction

class `factory.LazyFunction` (*method_to_call*)

The *LazyFunction* is the simplest case where the value of an attribute does not depend on the object being built.

It takes as argument a function to call; that should not take any arguments and return a value.

```
class LogFactory(factory.Factory):
    class Meta:
        model = models.Log

    timestamp = factory.LazyFunction(datetime.now)
```

```
>>> LogFactory()
<Log: log at 2016-02-12 17:02:34>

>>> # The LazyFunction can be overridden
>>> LogFactory(timestamp=now - timedelta(days=1))
<Log: log at 2016-02-11 17:02:34>
```

LazyFunction is also useful for assigning copies of mutable objects (like lists) to an object's property. Example:

```
DEFAULT_TEAM = ['Player1', 'Player2']

class TeamFactory(factory.Factory):
    class Meta:
        model = models.Team

    teammates = factory.LazyFunction(lambda: list(DEFAULT_TEAM))
```

Decorator

The class *LazyFunction* does not provide a decorator.

For complex cases, use `LazyAttribute.lazy_attribute()` directly.

LazyAttribute

class `factory.LazyAttribute` (*method_to_call*)

The *LazyAttribute* is a simple yet extremely powerful building brick for extending a *Factory*.

It takes as argument a method to call (usually a lambda); that method should accept the object being built as sole argument, and return a value.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    username = 'john'
    email = factory.LazyAttribute(lambda o: '%s@example.com' % o.username)
```

```
>>> u = UserFactory()
>>> u.email
'john@example.com'

>>> u = UserFactory(username='leo')
>>> u.email
'leo@example.com'
```

The object passed to `LazyAttribute` is not an instance of the target class, but instead a `Resolver`: a temporary container that computes the value of all declared fields.

Decorator

`factory.lazy_attribute()`

If a simple lambda isn't enough, you may use the `lazy_attribute()` decorator instead.

This decorates an instance method that should take a single argument, `self`; the name of the method will be used as the name of the attribute to fill with the return value of the method:

```
class UserFactory(factory.Factory)
    class Meta:
        model = User

    name = u"Jean"

    @factory.lazy_attribute
    def email(self):
        # Convert to plain ascii text
        clean_name = (unicodedata.normalize('NFKD', self.name)
                      .encode('ascii', 'ignore')
                      .decode('utf8'))

        return u'%s@example.com' % clean_name
```

```
>>> joel = UserFactory(name=u"Joël")
>>> joel.email
u'joel@example.com'
```

Sequence

`class factory.Sequence(lambda)`

If a field should be unique, and thus different for all built instances, use a `Sequence`.

This declaration takes a single argument, a function accepting a single parameter - the current sequence counter - and returning the related value.

```
class UserFactory(factory.Factory)
    class Meta:
        model = User

    phone = factory.Sequence(lambda n: '123-555-%04d' % n)
```

```
>>> UserFactory().phone
'123-555-0001'
>>> UserFactory().phone
'123-555-0002'
```

Decorator

factory.**sequence**()

As with *lazy_attribute()*, a decorator is available for complex situations.

sequence() decorates an instance method, whose *self* method will actually be the sequence counter - this might be confusing:

```
class UserFactory(factory.Factory)
    class Meta:
        model = User

    @factory.sequence
    def phone(n):
        a = n // 10000
        b = n % 10000
        return '%03d-555-%04d' % (a, b)
```

```
>>> UserFactory().phone
'000-555-9999'
>>> UserFactory().phone
'001-555-0000'
```

Sharing

The sequence counter is shared across all *Sequence* attributes of the *Factory*:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    phone = factory.Sequence(lambda n: '%04d' % n)
    office = factory.Sequence(lambda n: 'A23-B%03d' % n)
```

```
>>> u = UserFactory()
>>> u.phone, u.office
'0041', 'A23-B041'
>>> u2 = UserFactory()
>>> u2.phone, u2.office
'0042', 'A23-B042'
```

Inheritance

When a *Factory* inherits from another *Factory* and the *model* of the subclass inherits from the *model* of the parent, the sequence counter is shared across the *Factory* classes:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    phone = factory.Sequence(lambda n: '123-555-%04d' % n)

class EmployeeFactory(UserFactory):
    office_phone = factory.Sequence(lambda n: '%04d' % n)
```

```
>>> u = UserFactory()
>>> u.phone
'123-555-0001'

>>> e = EmployeeFactory()
>>> e.phone, e.office_phone
'123-555-0002', '0002'

>>> u2 = UserFactory()
>>> u2.phone
'123-555-0003'
```

Forcing a sequence counter

If a specific value of the sequence counter is required for one instance, the `__sequence` keyword argument should be passed to the factory method.

This will force the sequence counter during the call, without altering the class-level value.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    uid = factory.Sequence(int)
```

```
>>> UserFactory()
<User: 0>
>>> UserFactory()
<User: 1>
>>> UserFactory(__sequence=42)
<User: 42>
```

Warning: The impact of setting `__sequence=n` on a `_batch` call is undefined. Each generated instance may share a same counter, or use incremental values starting from the forced value.

LazyAttributeSequence

```
class factory.LazyAttributeSequence(method_to_call)
```

The `LazyAttributeSequence` declaration merges features of `Sequence` and `LazyAttribute`.

It takes a single argument, a function whose two parameters are, in order:

- The object being built
- The sequence counter

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    login = 'john'
    email = factory.LazyAttributeSequence(lambda o, n: '%s@s%d.example.com' % (o.
↪login, n))
```

```
>>> UserFactory().email
'john@s1.example.com'
>>> UserFactory(login='jack').email
'jack@s2.example.com'
```

Decorator

`factory.lazy_attribute_sequence` (*method_to_call*)

As for `lazy_attribute()` and `sequence()`, the `lazy_attribute_sequence()` handles more complex cases:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    login = 'john'

    @lazy_attribute_sequence
    def email(self, n):
        bucket = n % 10
        return '%s@s%d.example.com' % (self.login, bucket)
```

SubFactory

`class factory.SubFactory` (*factory, **kwargs*)

This attribute declaration calls another `Factory` subclass, selecting the same build strategy and collecting extra kwargs in the process.

The `SubFactory` attribute should be called with:

- A `Factory` subclass as first argument, or the fully qualified import path to that `Factory` (see *Circular imports*)
- An optional set of keyword arguments that should be passed when calling that factory

Note: When passing an actual `Factory` for the `factory` argument, make sure to pass the class and not instance (i.e no `()` after the class):


```
class FooFactory(factory.Factory):
    class Meta:
        model = Foo

    bar = factory.SubFactory(BarFactory) # Not BarFactory()
```

Definition

```
# A standard factory
class UserFactory(factory.Factory):
    class Meta:
        model = User

    # Various fields
    first_name = 'John'
    last_name = factory.Sequence(lambda n: 'D%se' % ('o' * n)) # De, Doe, Dooe,
↪Doooe, ...
    email = factory.LazyAttribute(lambda o: '%s.%s@example.org' % (o.first_name.
↪lower(), o.last_name.lower()))

# A factory for an object with a 'User' field
class CompanyFactory(factory.Factory):
    class Meta:
        model = Company

    name = factory.Sequence(lambda n: 'FactoryBoyz' + 'z' * n)

    # Let's use our UserFactory to create that user, and override its first name.
    owner = factory.SubFactory(UserFactory, first_name='Jack')
```

Calling

The wrapping factory will call of the inner factory:

```
>>> c = CompanyFactory()
>>> c
<Company: FactoryBoyz>

# Notice that the first_name was overridden
>>> c.owner
<User: Jack De>
>>> c.owner.email
jack.de@example.org
```

Fields of the *SubFactory* may be overridden from the external factory:

```
>>> c = CompanyFactory(owner__first_name='Henry')
>>> c.owner
<User: Henry Doe>

# Notice that the updated first_name was propagated to the email LazyAttribute.
>>> c.owner.email
```

(continues on next page)

(continued from previous page)

```
henry.doe@example.org

# It is also possible to override other fields of the SubFactory
>>> c = CompanyFactory(owner__last_name='Jones')
>>> c.owner
<User: Henry Jones>
>>> c.owner.email
henry.jones@example.org
```

Strategies

The strategy chosen for the external factory will be propagated to all subfactories:

```
>>> c = CompanyFactory()
>>> c.pk          # Saved to the database
3
>>> c.owner.pk   # Saved to the database
8

>>> c = CompanyFactory.build()
>>> c.pk          # Not saved
None
>>> c.owner.pk   # Not saved either
None
```

Circular imports

Some factories may rely on each other in a circular manner. This issue can be handled by passing the absolute import path to the target *Factory* to the *SubFactory*.

New in version 1.3.0.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    username = 'john'
    main_group = factory.SubFactory('users.factories.GroupFactory')

class GroupFactory(factory.Factory):
    class Meta:
        model = Group

    name = "MyGroup"
    owner = factory.SubFactory(UserFactory)
```

Obviously, such circular relationships require careful handling of loops:

```
>>> owner = UserFactory(main_group=None)
>>> UserFactory(main_group__owner=owner)
<john (group: MyGroup)>
```

SelfAttribute

class `factory.SelfAttribute` (*dotted_path_to_attribute*)

Some fields should reference another field of the object being constructed, or an attribute thereof.

This is performed by the `SelfAttribute` declaration. That declaration takes a single argument, a dot-delimited path to the attribute to fetch:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    birthdate = factory.Sequence(lambda n: datetime.date(2000, 1, 1) + datetime.
↳timedelta(days=n))
    birthmonth = factory.SelfAttribute('birthdate.month')
```

```
>>> u = UserFactory()
>>> u.birthdate
date(2000, 3, 15)
>>> u.birthmonth
3
```

Parents

When used in conjunction with `SubFactory`, the `SelfAttribute` gains an “upward” semantic through the double-dot notation, as used in Python imports.

`factory.SelfAttribute('..country.language')` means “Select the language of the country of the `Factory` calling me”.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    language = 'en'

class CompanyFactory(factory.Factory):
    class Meta:
        model = Company

    country = factory.SubFactory(CountryFactory)
    owner = factory.SubFactory(UserFactory, language=factory.SelfAttribute('..country.
↳language'))
```

```
>>> company = CompanyFactory()
>>> company.country.language
'fr'
>>> company.owner.language
'fr'
```

Obviously, this “follow parents” ability also handles overriding some attributes on call:

```
>>> company = CompanyFactory(country=china)
>>> company.owner.language
'cn'
```

This feature is also available to *LazyAttribute* and *LazyAttributeSequence*, through the `factory_parent` attribute of the passed-in object:

```
class CompanyFactory(factory.Factory):
    class Meta:
        model = Company
        country = factory.SubFactory(CountryFactory)
        owner = factory.SubFactory(UserFactory,
            language=factory.LazyAttribute(lambda user: user.factory_parent.country.
→ language),
        )
```

Iterator

class `factory.Iterator` (*iterable*, *cycle=True*, *getter=None*)

The *Iterator* declaration takes successive values from the given iterable. When it is exhausted, it starts again from zero (unless `cycle=False`).

cycle

The `cycle` argument is only useful for advanced cases, where the provided iterable has no end (as wishing to cycle it means storing values in memory...).

New in version 1.3.0: The `cycle` argument is available as of v1.3.0; previous versions had a behaviour equivalent to `cycle=False`.

getter

A custom function called on each value returned by the iterable. See the *Getter* section for details.

New in version 1.3.0.

reset ()

Reset the internal iterator used by the attribute, so that the next value will be the first value generated by the iterator.

May be called several times.

Each call to the factory will receive the next value from the iterable:

```
class UserFactory(factory.Factory)
    lang = factory.Iterator(['en', 'fr', 'es', 'it', 'de'])
```

```
>>> UserFactory().lang
'en'
>>> UserFactory().lang
'fr'
```

When a value is passed in for the argument, the iterator will *not* be advanced:

```
>>> UserFactory().lang
'en'
>>> UserFactory(lang='cn').lang
'cn'
>>> UserFactory().lang
'fr'
```

Getter

Some situations may reuse an existing iterable, using only some component. This is handled by the `getter` attribute: this is a function that accepts as sole parameter a value from the iterable, and returns an adequate value.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    # CATEGORY_CHOICES is a list of (key, title) tuples
    category = factory.Iterator(User.CATEGORY_CHOICES, getter=lambda c: c[0])
```

Decorator

`factory.iterator(func)`

When generating items of the iterator gets too complex for a simple list comprehension, use the `iterator()` decorator:

Warning: The decorated function takes **no** argument, notably no `self` parameter.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    @factory.iterator
    def name():
        with open('test/data/names.dat', 'r') as f:
            for line in f:
                yield line
```

Warning: Values from the underlying iterator are *kept* in memory; once the initial iterator has been emptied, saved values are used instead of executing the function instead.

Use `factory.Iterator(my_func, cycle=False)` to disable value recycling.

Resetting

In order to start back at the first value in an `Iterator`, simply call the `reset()` method of that attribute (accessing it from the bare `Factory` subclass):

```
>>> UserFactory().lang
'en'
>>> UserFactory().lang
'fr'
>>> UserFactory.lang.reset()
>>> UserFactory().lang
'en'
```

Dict and List

When a factory expects lists or dicts as arguments, such values can be generated through the whole range of `factory_boy` declarations, with the `Dict` and `List` attributes:

class `factory.Dict` (*params*[, *dict_factory*=`factory.DictFactory`])

The `Dict` class is used for dict-like attributes. It receives as non-keyword argument a dictionary of fields to define, whose value may be any factory-enabled declarations:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    is_superuser = False
    roles = factory.Dict({
        'role1': True,
        'role2': False,
        'role3': factory.Iterator([True, False]),
        'admin': factory.SelfAttribute('..is_superuser'),
    })
```

Note: Declarations used as a `Dict` values are evaluated within that `Dict`'s context; this means that you must use the `..foo` syntax to access fields defined at the factory level.

On the other hand, the `Sequence` counter is aligned on the containing factory's one.

The `Dict` behaviour can be tuned through the following parameters:

dict_factory

The actual factory to use for generating the dict can be set as a keyword argument, if an exotic dictionary-like object (`SortedDict`, ...) is required.

class `factory.List` (*items*[, *list_factory*=`factory.ListFactory`])

The `List` can be used for list-like attributes.

Internally, the fields are converted into a `index=value` dict, which makes it possible to override some values at use time:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    flags = factory.List([
        'user',
        'active',
        'admin',
    ])
```

```
>>> u = UserFactory(flags__2='superadmin')
>>> u.flags
['user', 'active', 'superadmin']
```

The `List` behaviour can be tuned through the following parameters:

list_factory

The actual factory to use for generating the list can be set as a keyword argument, if another type (tuple, set, ...) is required.

Maybe

class `factory.Maybe` (*decider, yes_declaration, no_declaration*)

Sometimes, the way to build a given field depends on the value of another, for instance of a parameter.

In those cases, use the *Maybe* declaration: it takes the name of a “decider” boolean field, and two declarations; depending on the value of the field whose name is held in the ‘decider’ parameter, it will apply the effects of one or the other declaration:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    is_active = True
    deactivation_date = factory.Maybe(
        'is_active',
        yes_declaration=None,
        no_declaration=factory.fuzzy.FuzzyDateTime(timezone.now() - datetime.
↳timedelta(days=10)),
    )
```

```
>>> u = UserFactory(is_active=True)
>>> u.deactivation_date
None
>>> u = UserFactory(is_active=False)
>>> u.deactivation_date
datetime.datetime(2017, 4, 1, 23, 21, 23, tzinfo=UTC)
```

Note: If the condition for the decider is complex, use a *LazyAttribute* defined in the *Params* section of your factory to handle the computation.

Post-generation hooks

Some objects expect additional method calls or complex processing for proper definition. For instance, a `User` may need to have a related `Profile`, where the `Profile` is built from the `User` object.

To support this pattern, factory_boy provides the following tools:

- *PostGenerationMethodCall*: allows you to hook a particular attribute to a function call
- *PostGeneration*: this class allows calling a given function with the generated object as argument
- *post_generation()*: decorator performing the same functions as *PostGeneration*
- *RelatedFactory*: this builds or creates a given factory *after* building/creating the first Factory.
- *RelatedFactoryList*: this builds or creates a *list* of the given factory *after* building/creating the first Factory.

Post-generation hooks are called in the same order they are declared in the factory class, so that functions can rely on the side effects applied by the previous post-generation hook.

Extracting parameters

All post-building hooks share a common base for picking parameters from the set of attributes passed to the *Factory*.

For instance, a *PostGeneration* hook is declared as `post`:

```
class SomeFactory(factory.Factory):
    class Meta:
        model = SomeObject

    @post_generation
    def post(obj, create, extracted, **kwargs):
        obj.set_origin(create)
```

When calling the factory, some arguments will be extracted for this method:

- If a `post` argument is passed, it will be passed as the `extracted` field
- Any argument starting with `post__XYZ` will be extracted, its `post__` prefix removed, and added to the `kwargs` passed to the post-generation hook.

Extracted arguments won't be passed to the *model* class.

Thus, in the following call:

```
>>> SomeFactory(
    post=1,
    post_x=2,
    post__y=3,
    post__z__t=42,
)
```

The `post` hook will receive `1` as `extracted` and `{'y': 3, 'z__t': 42}` as keyword arguments; `{'post_x': 2}` will be passed to `SomeFactory._meta.model`.

RelatedFactory

class `factory.RelatedFactory` (*factory*, *factory_related_name*="", ***kwargs*)

A *RelatedFactory* behaves mostly like a *SubFactory*, with the main difference that the related *Factory* will be generated *after* the base *Factory*.

factory

As for *SubFactory*, the *factory* argument can be:

- A *Factory* subclass
- Or the fully qualified path to a *Factory* subclass (see *Circular imports* for details)

name

The generated object (where the *RelatedFactory* attribute will set) may be passed to the related factory if the *factory_related_name* parameter is set.

It will be passed as a keyword argument, using the *name* value as keyword:

```
class CityFactory(factory.Factory):
    class Meta:
        model = City

    capital_of = None
    name = "Toronto"

class CountryFactory(factory.Factory):
    class Meta:
```

(continues on next page)

(continued from previous page)

```

    model = Country

    lang = 'fr'
    capital_city = factory.RelatedFactory(
        CityFactory, # Not CityFactory()
        'capital_of',
        name="Paris",
    )

```

```

>>> france = CountryFactory()
>>> City.objects.get(capital_of=france)
<City: Paris>

```

Extra kwargs may be passed to the related factory, through the usual `ATTR__SUBATTR` syntax:

```

>>> england = CountryFactory(lang='en', capital_city__name="London")
>>> City.objects.get(capital_of=england)
<City: London>

```

If a value is passed for the `RelatedFactory` attribute, this disables `RelatedFactory` generation:

```

>>> france = CountryFactory()
>>> paris = City.objects.get()
>>> paris
<City: Paris>
>>> reunion = CountryFactory(capital_city=paris)
>>> City.objects.count() # No new capital_city generated
1
>>> guyane = CountryFactory(capital_city=paris, capital_city__name='Kourou')
>>> City.objects.count() # No new capital_city generated, ``name`` ignored.
1

```

Note: The target of the `RelatedFactory` is evaluated *after* the initial factory has been instantiated. However, the build context is passed down to that factory; this means that calls to `factory.SelfAttribute` can go back to the calling factory's context:

```

class CountryFactory(factory.Factory):
    class Meta:
        model = Country

    lang = 'fr'
    capital_city = factory.RelatedFactory(CityFactory, 'capital_of',
        # Would also work with SelfAttribute('capital_of.lang')
        main_lang=factory.SelfAttribute('..lang'),
    )

```

RelatedFactoryList

class `factory.RelatedFactoryList` (*factory, factory_related_name=""*, *size=2*, ***kwargs*)

A `RelatedFactoryList` behaves like a `RelatedFactory`, only it returns a list of factories. This is useful for simulating one-to-many relations, rather than the one-to-one relation generated by `RelatedFactory`.

factory

As for *SubFactory*, the *factory* argument can be:

- A *Factory* subclass
- Or the fully qualified path to a *Factory* subclass (see *Circular imports* for details)

name

The generated object (where the *RelatedFactory* attribute will set) may be passed to the related factories if the *factory_related_name* parameter is set.

It will be passed as a keyword argument, using the *name* value as keyword:

size

Either an *int*, or a *lambda* that returns an *int*, which will define the number of related Factories to be generated for each parent object.

New in version 2.12: Note that the API for *RelatedFactoryList* is considered experimental, and might change in a future version for increased consistency with other declarations.

Note: Note that using a *lambda* for *size* allows the number of related objects per parents object to vary. This is useful for testing, when you likely don't want your mock data to have parent objects with the exact same, static number of related objects.

```
LIST_SIZES = [1, 2, 3, 4, 5]

class FooFactory(factory.Factory):
    class Meta:
        model = Foo
        # Generate a list of `factory` objects of random size, ranging from 1 -> 5
        bar = factory.RelatedFactoryList(BarFactory,
                                         size=lambda: LIST_SIZES[random.randint(0,5)])
        # Each Foo object will have exactly 3 Bar objects generated for its foobar_
        ↪attribute.
        foobar = factory.RelatedFactoryList(BarFactory, size=3)
```

PostGeneration

class `factory.PostGeneration` (*callable*)

The *PostGeneration* declaration performs actions once the model object has been generated.

Its sole argument is a callable, that will be called once the base object has been generated.

Once the base object has been generated, the provided callable will be called as `callable(obj, create, extracted, **kwargs)`, where:

- *obj* is the base object previously generated
- *create* is a boolean indicating which strategy was used
- *extracted* is *None* unless a value was passed in for the *PostGeneration* declaration at *Factory* declaration time
- *kwargs* are any extra parameters passed as `attr__key=value` when calling the *Factory*:

```
class UserFactory(factory.Factory):
    class Meta:
        model = User
```

(continues on next page)

(continued from previous page)

```
login = 'john'
make_mbox = factory.PostGeneration(
    lambda obj, create, extracted, **kwargs: os.makedirs(obj.login))
```

Decorator

`factory.post_generation()`

A decorator is also provided, decorating a single method accepting the same `obj`, `create`, `extracted` and keyword arguments as `PostGeneration`.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    login = 'john'

    @factory.post_generation
    def mbox(obj, create, extracted, **kwargs):
        if not create:
            return
        path = extracted or os.path.join('/tmp/mbox/', obj.login)
        os.path.makedirs(path)
        return path
```

```
>>> UserFactory.build()           # Nothing was created
>>> UserFactory.create()          # Creates dir /tmp/mbox/john
>>> UserFactory.create(login='jack') # Creates dir /tmp/mbox/jack
>>> UserFactory.create(mbox='/tmp/alt') # Creates dir /tmp/alt
```

PostGenerationMethodCall

`class factory.PostGenerationMethodCall(method_name, *arg, **kwargs)`

The `PostGenerationMethodCall` declaration will call a method on the generated object just after instantiation. This declaration class provides a friendly means of generating attributes of a factory instance during initialization. The declaration is created using the following arguments:

method_name

The name of the method to call on the `model` object

arg

The default, optional, positional argument to pass to the method given in `method_name`

kwargs

The default set of keyword arguments to pass to the method given in `method_name`

Once the factory instance has been generated, the method specified in `method_name` will be called on the generated object with any arguments specified in the `PostGenerationMethodCall` declaration, by default.

For example, to set a default password on a generated `User` instance during instantiation, we could make a declaration for a `password` attribute like below:

```
class UserFactory(factory.Factory):
    class Meta:
```

(continues on next page)

(continued from previous page)

```

    model = User

    username = 'user'
    password = factory.PostGenerationMethodCall('set_password',
                                                'defaultpassword')

```

When we instantiate a user from the `UserFactory`, the factory will create a password attribute by calling `User.set_password('defaultpassword')`. Thus, by default, our users will have a password set to `'defaultpassword'`.

```

>>> u = UserFactory() # Calls user.set_password(
↳ 'defaultpassword')
>>> u.check_password('defaultpassword')
True

```

If the `PostGenerationMethodCall` declaration contained no arguments or one argument, an overriding value can be passed directly to the method through a keyword argument matching the attribute name. For example we can override the default password specified in the declaration above by simply passing in the desired password as a keyword argument to the factory during instantiation.

```

>>> other_u = UserFactory(password='different') # Calls user.set_password('different
↳ ')
>>> other_u.check_password('defaultpassword')
False
>>> other_u.check_password('different')
True

```

Note: For Django models, unless the object method called by `PostGenerationMethodCall` saves the object back to the database, we will have to explicitly remember to save the object back if we performed a `create()`.

```

>>> u = UserFactory.create() # u.password has not been saved back to the database
>>> u.save() # we must remember to do it ourselves

```

We can avoid this by subclassing from `DjangoModelFactory`, instead, e.g.,

```

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = User

    username = 'user'
    password = factory.PostGenerationMethodCall('set_password',
                                                'defaultpassword')

```

Warning: In order to keep a consistent and simple API, a `PostGenerationMethodCall` allows *at most one* positional argument; all other parameters should be passed as keyword arguments.

Keywords extracted from the factory arguments are merged into the defaults present in the `PostGenerationMethodCall` declaration.

```

>>> UserFactory(password__disabled=True) # Calls user.set_password('', 'sha1',
↳ disabled=True)

```

7.2.3 Module-level functions

Beyond the *Factory* class and the various *Declarations* classes and methods, `factory_boy` exposes a few module-level functions, mostly useful for lightweight factory generation.

Lightweight factory declaration

`factory.make_factory(klass, **kwargs)`

The `make_factory()` function takes a class, declarations as keyword arguments, and generates a new *Factory* for that class accordingly:

```
UserFactory = make_factory(User,
    login='john',
    email=factory.LazyAttribute(lambda u: '%s@example.com' % u.login),
)

# This is equivalent to:

class UserFactory(factory.Factory):
    class Meta:
        model = User

    login = 'john'
    email = factory.LazyAttribute(lambda u: '%s@example.com' % u.login)
```

An alternate base class to *Factory* can be specified in the `FACTORY_CLASS` argument:

```
UserFactory = make_factory(models.User,
    login='john',
    email=factory.LazyAttribute(lambda u: '%s@example.com' % u.login),
    FACTORY_CLASS=factory.django.DjangoModelFactory,
)

# This is equivalent to:

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    login = 'john'
    email = factory.LazyAttribute(lambda u: '%s@example.com' % u.login)
```

New in version 2.0.0: The `FACTORY_CLASS` kwarg was added in 2.0.0.

Instance building

The `factory` module provides a bunch of shortcuts for creating a factory and extracting instances from them. Helper methods can be used to create factories in a dynamic way based on parameters.

Internally, helper methods use `make_factory()` to create a new *Factory* and perform additional calls on the newly created *Factory* according to the method name.

Please note, that all *Factories* created with this methods inherit from the `factory.base.Factory` class. For full support of your ORM, specify a base class with the `FACTORY_CLASS` parameter as shown in `make_factory()` examples.

`factory.build(klass, FACTORY_CLASS=None, **kwargs)`

`factory.build_batch` (*klass*, *size*, *FACTORY_CLASS=None*, ***kwargs*)

Create a factory for *klass* using declarations passed in *kwargs*; return an instance built from that factory with *BUILD_STRATEGY*, or a list of *size* instances (for *build_batch()*).

Parameters

- **klass** (*class*) – Class of the instance to build
- **size** (*int*) – Number of instances to build
- **kwargs** – Declarations to use for the generated factory
- **FACTORY_CLASS** – Alternate base class (instead of *Factory*)

`factory.create` (*klass*, *FACTORY_CLASS=None*, ***kwargs*)

`factory.create_batch` (*klass*, *size*, *FACTORY_CLASS=None*, ***kwargs*)

Create a factory for *klass* using declarations passed in *kwargs*; return an instance created from that factory with *CREATE_STRATEGY*, or a list of *size* instances (for *create_batch()*).

Parameters

- **klass** (*class*) – Class of the instance to create
- **size** (*int*) – Number of instances to create
- **kwargs** – Declarations to use for the generated factory
- **FACTORY_CLASS** – Alternate base class (instead of *Factory*)

`factory.stub` (*klass*, *FACTORY_CLASS=None*, ***kwargs*)

`factory.stub_batch` (*klass*, *size*, *FACTORY_CLASS=None*, ***kwargs*)

Create a factory for *klass* using declarations passed in *kwargs*; return an instance stubbed from that factory with *STUB_STRATEGY*, or a list of *size* instances (for *stub_batch()*).

Parameters

- **klass** (*class*) – Class of the instance to stub
- **size** (*int*) – Number of instances to stub
- **kwargs** – Declarations to use for the generated factory
- **FACTORY_CLASS** – Alternate base class (instead of *Factory*)

`factory.generate` (*klass*, *strategy*, *FACTORY_CLASS=None*, ***kwargs*)

`factory.generate_batch` (*klass*, *strategy*, *size*, *FACTORY_CLASS=None*, ***kwargs*)

Create a factory for *klass* using declarations passed in *kwargs*; return an instance generated from that factory with the *strategy* strategy, or a list of *size* instances (for *generate_batch()*).

Parameters

- **klass** (*class*) – Class of the instance to generate
- **strategy** (*str*) – The strategy to use
- **size** (*int*) – Number of instances to generate
- **kwargs** – Declarations to use for the generated factory
- **FACTORY_CLASS** – Alternate base class (instead of *Factory*)

`factory.simple_generate` (*klass*, *create*, *FACTORY_CLASS=None*, ***kwargs*)

`factory.simple_generate_batch` (*klass*, *create*, *size*, *FACTORY_CLASS=None*, ***kwargs*)
 Create a factory for *klass* using declarations passed in *kwargs*; return an instance generated from that factory according to the *create* flag, or a list of *size* instances (for `simple_generate_batch()`).

Parameters

- **klass** (*class*) – Class of the instance to generate
- **create** (*bool*) – Whether to build (`False`) or create (`True`) instances
- **size** (*int*) – Number of instances to generate
- **kwargs** – Declarations to use for the generated factory
- **FACTORY_CLASS** – Alternate base class (instead of `Factory`)

7.2.4 Randomness management

Using `random` in factories allows to “fuzz” a program efficiently. However, it’s sometimes required to *reproduce* a failing test.

`factory.fuzzy` and `factory.Faker` share a dedicated instance of `random.Random`, which can be managed through the `factory.random` module:

`factory.random.get_random_state()`

Call `get_random_state()` to retrieve the random generator’s current state. This method synchronizes both `Faker`’s and `factory_boy`’s random state. The returned object is implementation-specific.

`factory.random.set_random_state(state)`

Use `set_random_state()` to set a custom state into the random generator (fetched from `get_random_state()` in a previous run, for instance)

`factory.random.reseed_random(seed)`

The `reseed_random()` function allows to load a chosen seed into the random generator. That seed can be anything accepted by `random.seed()`.

See *Using reproducible randomness* for help in using those methods in a test setup.

7.3 Using factory_boy with ORMs

`factory_boy` provides custom `Factory` subclasses for various ORMs, adding dedicated features.

7.3.1 Django

The first versions of `factory_boy` were designed specifically for Django, but the library has now evolved to be framework-independent.

Most features should thus feel quite familiar to Django users.

The DjangoModelFactory subclass

All factories for a Django `Model` should use the `DjangoModelFactory` base class.

```
class factory.django.DjangoModelFactory(factory.Factory)
```

Dedicated class for Django `Model` factories.

This class provides the following features:

- The `model` attribute also supports the `'app.Model'` syntax
- `create()` uses `Model.objects.create()`
- When using `RelatedFactory` or `PostGeneration` attributes, the base object will be `saved` once all post-generation hooks have run.

class `factory.django.DjangoOptions` (*factory.base.FactoryOptions*)

The class `Meta` on a `DjangoModelFactory` supports extra parameters:

database

New in version 2.5.0.

All queries to the related model will be routed to the given database. It defaults to `'default'`.

django_get_or_create

New in version 2.4.0.

Fields whose name are passed in this list will be used to perform a `Model.objects.get_or_create()` instead of the usual `Model.objects.create()`:

```
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = 'myapp.User' # Equivalent to ``model = myapp.models.User``
        django_get_or_create = ('username',)

    username = 'john'
```

```
>>> User.objects.all()
[]
>>> UserFactory() # Creates a new user
<User: john>
>>> User.objects.all()
[<User: john>]

>>> UserFactory() # Fetches the existing user
<User: john>
>>> User.objects.all() # No new user!
[<User: john>]

>>> UserFactory(username='jack') # Creates another user
<User: jack>
>>> User.objects.all()
[<User: john>, <User: jack>]
```

Extra fields

class `factory.django.FileField`

Custom declarations for `django.db.models.FileField`

`__init__` (*self*, *from_path*=",*from_file*=",*from_func*=",*data=b*",*filename*='example.dat')

Parameters

- **from_path** (*str*) – Use data from the file located at *from_path*, and keep its filename
- **from_file** (*file*) – Use the contents of the provided file object; use its filename if available, unless *filename* is also provided.
- **from_func** (*func*) – Use function that returns a file object

- **data** (*bytes*) – Use the provided bytes as file contents
- **filename** (*str*) – The filename for the FileField

Note: If the value `None` was passed for the `FileField` field, this will disable field generation:

```
class MyFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.MyModel

    the_file = factory.django.FileField(filename='the_file.dat')
```

```
>>> MyFactory(the_file__data=b'uhuh').the_file.read()
b'uhuh'
>>> MyFactory(the_file=None).the_file
None
```

class factory.django.ImageField

Custom declarations for `django.db.models.ImageField`

```
__init__(self, from_path="", from_file="", from_func="", filename='example.jpg', width=100,
          height=100, color='green', format='JPEG')
```

Parameters

- **from_path** (*str*) – Use data from the file located at `from_path`, and keep its filename
- **from_file** (*file*) – Use the contents of the provided file object; use its filename if available
- **from_func** (*func*) – Use function that returns a file object
- **filename** (*str*) – The filename for the ImageField
- **width** (*int*) – The width of the generated image (default: 100)
- **height** (*int*) – The height of the generated image (default: 100)
- **color** (*str*) – The color of the generated image (default: 'green')
- **format** (*str*) – The image format (as supported by PIL) (default: 'JPEG')
- **palette** (*str*) – The image palette (as supported by PIL) (default: 'RGB')

Note: If the value `None` was passed for the `FileField` field, this will disable field generation:

Note: Just as Django's `django.db.models.ImageField` requires the Python Imaging Library, this `ImageField` requires it too.

```
class MyFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.MyModel

    the_image = factory.django.ImageField(color='blue')
```

```
>>> MyFactory(the_image__width=42).the_image.width
42
>>> MyFactory(the_image=None).the_image
None
```

Disabling signals

Signals are often used to plug some custom code into external components code; for instance to create `Profile` objects on-the-fly when a new `User` object is saved.

This may interfere with finely tuned *factories*, which would create both using *RelatedFactory*.

To work around this problem, use the `mute_signals()` decorator/context manager:

```
factory.django.mute_signals(signal1, ...)
```

Disable the list of selected signals when calling the factory, and reactivate them upon leaving.

```
# foo/factories.py

import factory

from . import models
from . import signals

@factory.django.mute_signals(signals.pre_save, signals.post_save)
class FooFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Foo

    # ...

def make_chain():
    with factory.django.mute_signals(signals.pre_save, signals.post_save):
        # pre_save/post_save won't be called here.
        return SomeFactory(), SomeOtherFactory()
```

7.3.2 Mogo

factory_boy supports *Mogo*-style models, through the *MogoFactory* class.

Mogo is a wrapper around the `pymongo` library for MongoDB.

```
class factory.mogo.MogoFactory(factory.Factory)
    Dedicated class for Mogo models.
```

This class provides the following features:

- `build()` calls a model's `new()` method
- `create()` builds an instance through `new()` then saves it.

7.3.3 MongoEngine

factory_boy supports *MongoEngine*-style models, through the *MongoEngineFactory* class.

`mongoengine` is a wrapper around the `pymongo` library for MongoDB.

class `factory.mongoengine.MongoEngineFactory` (*factory.Factory*)
 Dedicated class for `MongoEngine` models.

This class provides the following features:

- `build()` calls a model's `__init__` method
- `create()` builds an instance through `__init__` then saves it.

Note: If the associated class `<factory.FactoryOptions.model` is a `mongoengine.EmbeddedDocument`, the `create()` function won't "save" it, since this wouldn't make sense.

This feature makes it possible to use `SubFactory` to create embedded document.

A minimalist example:

```
import mongoengine

class Address(mongoengine.EmbeddedDocument):
    street = mongoengine.StringField()

class Person(mongoengine.Document):
    name = mongoengine.StringField()
    address = mongoengine.EmbeddedDocumentField(Address)

import factory

class AddressFactory(factory.mongoengine.MongoEngineFactory):
    class Meta:
        model = Address

    street = factory.Sequence(lambda n: 'street%d' % n)

class PersonFactory(factory.mongoengine.MongoEngineFactory):
    class Meta:
        model = Person

    name = factory.Sequence(lambda n: 'name%d' % n)
    address = factory.SubFactory(AddressFactory)
```

7.3.4 SQLAlchemy

Factory_boy also supports `SQLAlchemy` models through the `SQLAlchemyModelFactory` class.

To work, this class needs an `SQLAlchemy` session object affected to the `Meta.sqlalchemy_session` attribute.

class `factory.alchemy.SQLAlchemyModelFactory` (*factory.Factory*)
 Dedicated class for `SQLAlchemy` models.

This class provides the following features:

- `create()` uses `sqlalchemy.orm.session.Session.add()`

class `factory.alchemy.SQLAlchemyOptions` (*factory.base.FactoryOptions*)

In addition to the usual parameters available in class `Meta`, a `SQLAlchemyModelFactory` also supports the following settings:

sqlalchemy_session

SQLAlchemy session to use to communicate with the database when creating an object through this *SQLAlchemyModelFactory*.

sqlalchemy_session_persistence

Control the action taken by sqlalchemy session at the end of a create call.

Valid values are:

- None: do nothing
- 'flush': perform a session `flush()`
- 'commit': perform a session `commit()`

The default value is None.

If `force_flush` is set to `True`, it overrides this option.

force_flush

Force a session `flush()` at the end of `_create()`.

Note: This option is deprecated. Use `sqlalchemy_session_persistence` instead.

A (very) simple example:

```
from sqlalchemy import Column, Integer, Unicode, create_engine
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.orm import scoped_session, sessionmaker

engine = create_engine('sqlite://')
session = scoped_session(sessionmaker(bind=engine))
Base = declarative_base()

class User(Base):
    """ A SQLAlchemy simple model class who represents a user """
    __tablename__ = 'UserTable'

    id = Column(Integer(), primary_key=True)
    name = Column(Unicode(20))

Base.metadata.create_all(engine)

import factory

class UserFactory(factory.alchemy.SQLAlchemyModelFactory):
    class Meta:
        model = User
        sqlalchemy_session = session # the SQLAlchemy session object

    id = factory.Sequence(lambda n: n)
    name = factory.Sequence(lambda n: u'User %d' % n)
```

```
>>> session.query(User).all()
[]
>>> UserFactory()
<User: User 1>
```

(continues on next page)

(continued from previous page)

```
>>> session.query(User).all()
[<User: User 1>]
```

Managing sessions

Since `SQLAlchemy` is a general purpose library, there is no “global” session management system.

The most common pattern when working with unit tests and `factory_boy` is to use `SQLAlchemy`’s `sqlalchemy.orm.scoping.scoped_session`:

- The test runner configures some project-wide `scoped_session`
- Each `SQLAlchemyModelFactory` subclass uses this `scoped_session` as its `sqlalchemy_session`
- The `tearDown()` method of tests calls `Session.remove` to reset the session.

Note: See the excellent [SQLAlchemy guide on `scoped_session`](#) for details of `scoped_session`’s usage.

The basic idea is that declarative parts of the code (including factories) need a simple way to access the “current session”, but that session will only be created and configured at a later point.

The `scoped_session` handles this, by virtue of only creating the session when a query is sent to the database.

Here is an example layout:

- A global (test-only?) file holds the `scoped_session`:

```
# myprojet/test/common.py

from sqlalchemy import orm
Session = orm.scoped_session(orm.sessionmaker())
```

- All factory access it:

```
# myproject/factories.py

import factory

from . import models
from .test import common

class UserFactory(factory.alchemy.SQLAlchemyModelFactory):
    class Meta:
        model = models.User

        # Use the not-so-global scoped_session
        # Warning: DO NOT USE common.Session()!
        sqlalchemy_session = common.Session

    name = factory.Sequence(lambda n: "User %d" % n)
```

- The test runner configures the `scoped_session` when it starts:

```
# myproject/test/runtests.py

import sqlalchemy
```

(continues on next page)

(continued from previous page)

```

from . import common

def runtests():
    engine = sqlalchemy.create_engine('sqlite://')

    # It's a scoped_session, and now is the time to configure it.
    common.Session.configure(bind=engine)

    run_the_tests

```

- test cases use this `scoped_session`, and clear it after each test (for isolation):

```

# myproject/test/test_stuff.py

import unittest

from . import common

class MyTest(unittest.TestCase):

    def setUp(self):
        # Prepare a new, clean session
        self.session = common.Session()

    def test_something(self):
        u = factories.UserFactory()
        self.assertEqual([u], self.session.query(User).all())

    def tearDown(self):
        # Rollback the session => no changes to the database
        self.session.rollback()
        # Remove it, so that the next test gets a new Session()
        common.Session.remove()

```

7.4 Common recipes

Note: Most recipes below take on Django model examples, but can also be used on their own.

7.4.1 Dependent objects (ForeignKey)

When one attribute is actually a complex field (e.g a `ForeignKey` to another `Model`), use the `SubFactory` declaration:

```

# models.py
class User(models.Model):
    first_name = models.CharField()
    group = models.ForeignKey(Group)

```

(continues on next page)

(continued from previous page)

```
# factories.py
import factory
from . import models

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    first_name = factory.Sequence(lambda n: "Agent %03d" % n)
    group = factory.SubFactory(GroupFactory)
```

Choosing from a populated table

If the target of the `ForeignKey` should be chosen from a pre-populated table (e.g `django.contrib.contenttypes.models.ContentType`), simply use a `factory.Iterator` on the chosen queryset:

```
import factory, factory.django
from . import models

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    language = factory.Iterator(models.Language.objects.all())
```

Here, `models.Language.objects.all()` won't be evaluated until the first call to `UserFactory`; thus avoiding DB queries at import time.

7.4.2 Reverse dependencies (reverse ForeignKey)

When a related object should be created upon object creation (e.g a reverse `ForeignKey` from another `Model`), use a `RelatedFactory` declaration:

```
# models.py
class User(models.Model):
    pass

class UserLog(models.Model):
    user = models.ForeignKey(User)
    action = models.CharField()

# factories.py
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    log = factory.RelatedFactory(UserLogFactory, 'user', action=models.UserLog.ACTION_
↪CREATE)
```

When a `UserFactory` is instantiated, `factory_boy` will call `UserLogFactory(user=that_user, action=...)` just before returning the created `User`.

Example: Django's Profile

Django (<1.5) provided a mechanism to attach a `Profile` to a `User` instance, using a `OneToOneField` from the `Profile` to the `User`.

A typical way to create those profiles was to hook a post-save signal to the `User` model.

Prior to version 2.9, the solution to this was to override the `_generate()` method on the factory.

Since version 2.9, the `mute_signals()` decorator should be used:

```
@factory.django.mute_signals(post_save)
class ProfileFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = my_models.Profile

        title = 'Dr'
        # We pass in profile=None to prevent UserFactory from creating another profile
        # (this disables the RelatedFactory)
        user = factory.SubFactory('app.factories.UserFactory', profile=None)

@factory.django.mute_signals(post_save)
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = auth_models.User

        username = factory.Sequence(lambda n: "user_%d" % n)

        # We pass in 'user' to link the generated Profile to our just-generated User
        # This will call ProfileFactory(user=our_new_user), thus skipping the SubFactory.
        profile = factory.RelatedFactory(ProfileFactory, 'user')
```

```
>>> u = UserFactory(profile__title=u"Lord")
>>> u.get_profile().title
u"Lord"
```

Such behaviour can be extended to other situations where a signal interferes with `factory_boy` related factories.

Any factories that call these classes with `SubFactory` will also need to be decorated in the same manner.

Note: When any `RelatedFactory` or `post_generation` attribute is defined on the `DjangoModelFactory` subclass, a second `save()` is performed *after* the call to `_create()`.

Code working with signals should thus use the `mute_signals()` decorator

7.4.3 Simple Many-to-many relationship

Building the adequate link between two models depends heavily on the use case; `factory_boy` doesn't provide a "all in one tools" as for `SubFactory` or `RelatedFactory`, users will have to craft their own depending on the model.

The base building block for this feature is the `post_generation` hook:

```
# models.py
class Group(models.Model):
    name = models.CharField()
```

(continues on next page)

(continued from previous page)

```

class User(models.Model):
    name = models.CharField()
    groups = models.ManyToManyField(Group)

# factories.py
class GroupFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Group

    name = factory.Sequence(lambda n: "Group #s" % n)

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    name = "John Doe"

    @factory.post_generation
    def groups(self, create, extracted, **kwargs):
        if not create:
            # Simple build, do nothing.
            return

        if extracted:
            # A list of groups were passed in, use them
            for group in extracted:
                self.groups.add(group)

```

When calling `UserFactory()` or `UserFactory.build()`, no group binding will be created.

But when `UserFactory.create(groups=(group1, group2, group3))` is called, the groups declaration will add passed in groups to the set of groups for the user.

For SQLAlchemy, `list` is for many-to-many relationship. Modify `self.groups.add(group)` to `self.groups.append(group)` from the above example, then create `UserFactory.create(groups=[group1, group2, group3])`

7.4.4 Many-to-many relation with a ‘through’

If only one link is required, this can be simply performed with a `RelatedFactory`. If more links are needed, simply add more `RelatedFactory` declarations:

```

# models.py
class User(models.Model):
    name = models.CharField()

class Group(models.Model):
    name = models.CharField()
    members = models.ManyToManyField(User, through='GroupLevel')

class GroupLevel(models.Model):
    user = models.ForeignKey(User)
    group = models.ForeignKey(Group)
    rank = models.IntegerField()

```

(continues on next page)

(continued from previous page)

```

# factories.py
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

        name = "John Doe"

class GroupFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Group

        name = "Admins"

class GroupLevelFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.GroupLevel

        user = factory.SubFactory(UserFactory)
        group = factory.SubFactory(GroupFactory)
        rank = 1

class UserWithGroupFactory(UserFactory):
    membership = factory.RelatedFactory(GroupLevelFactory, 'user')

class UserWith2GroupsFactory(UserFactory):
    membership1 = factory.RelatedFactory(GroupLevelFactory, 'user', group__name=
↪ 'Group1')
    membership2 = factory.RelatedFactory(GroupLevelFactory, 'user', group__name=
↪ 'Group2')

```

Whenever the `UserWithGroupFactory` is called, it will, as a post-generation hook, call the `GroupLevelFactory`, passing the generated user as a user field:

1. `UserWithGroupFactory()` generates a `User` instance, `obj`
2. It calls `GroupLevelFactory(user=obj)`
3. It returns `obj`

When using the `UserWith2GroupsFactory`, that behavior becomes:

1. `UserWith2GroupsFactory()` generates a `User` instance, `obj`
2. It calls `GroupLevelFactory(user=obj, group__name='Group1')`
3. It calls `GroupLevelFactory(user=obj, group__name='Group2')`
4. It returns `obj`

7.4.5 Copying fields to a SubFactory

When a field of a related class should match one of the container:

```

# models.py
class Country(models.Model):
    name = models.CharField()
    lang = models.CharField()

```

(continues on next page)

(continued from previous page)

```

class User(models.Model):
    name = models.CharField()
    lang = models.CharField()
    country = models.ForeignKey(Country)

class Company(models.Model):
    name = models.CharField()
    owner = models.ForeignKey(User)
    country = models.ForeignKey(Country)

```

Here, we want:

- The User to have the lang of its country (`factory.SelfAttribute('country.lang')`)
- The Company owner to live in the country of the company (`factory.SelfAttribute('..country')`)

```

# factories.py
class CountryFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Country

    name = factory.Iterator(["France", "Italy", "Spain"])
    lang = factory.Iterator(['fr', 'it', 'es'])

class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    name = "John"
    lang = factory.SelfAttribute('country.lang')
    country = factory.SubFactory(CountryFactory)

class CompanyFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Company

    name = "ACME, Inc."
    country = factory.SubFactory(CountryFactory)
    owner = factory.SubFactory(UserFactory, country=factory.SelfAttribute('..country
↪'))

```

If the value of a field on the child factory is indirectly derived from a field on the parent factory, you will need to use `LazyAttribute` and poke the “`factory_parent`” attribute.

This time, we want the company owner to live in a country neighboring the country of the company:

```

class CompanyFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Company

    name = "ACME, Inc."
    country = factory.SubFactory(CountryFactory)
    owner = factory.SubFactory(UserFactory,
        country=factory.LazyAttribute(lambda o: get_random_neighbor(o.factory_parent.
↪country)))

```

7.4.6 Custom manager methods

Sometimes you need a factory to call a specific manager method other than the default `Model.objects.create()` method:

```
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = UserenaSignup

    username = "l7d8s"
    email = "my_name@example.com"
    password = "my_password"

    @classmethod
    def _create(cls, model_class, *args, **kwargs):
        """Override the default ``_create`` with our custom call."""
        manager = cls._get_manager(model_class)
        # The default would use ``manager.create(*args, **kwargs)``
        return manager.create_user(*args, **kwargs)
```

7.4.7 Forcing the sequence counter

A common pattern with `factory_boy` is to use a `factory.Sequence` declaration to provide varying values to attributes declared as unique.

However, it is sometimes useful to force a given value to the counter, for instance to ensure that tests are properly reproducible.

`factory_boy` provides a few hooks for this:

Forcing the value on a per-call basis In order to force the counter for a specific `Factory` instantiation, just pass the value in the `__sequence=42` parameter:

```
class AccountFactory(factory.Factory):
    class Meta:
        model = Account
        uid = factory.Sequence(lambda n: n)
        name = "Test"

>>> obj1 = AccountFactory(name="John Doe", __sequence=10)
>>> obj1.uid # Taken from the __sequence counter
10
>>> obj2 = AccountFactory(name="Jane Doe")
>>> obj2.uid # The base sequence counter hasn't changed
1
```

Resetting the counter globally If all calls for a factory must start from a deterministic number, use `factory.Factory.reset_sequence()`; this will reset the counter to its initial value (as defined by `factory.Factory._setup_next_sequence()`).

```
>>> AccountFactory().uid
1
>>> AccountFactory().uid
2
>>> AccountFactory.reset_sequence()
>>> AccountFactory().uid # Reset to the initial value
```

(continues on next page)

(continued from previous page)

```
1
>>> AccountFactory().uid
2
```

It is also possible to reset the counter to a specific value:

```
>>> AccountFactory.reset_sequence(10)
>>> AccountFactory().uid
10
>>> AccountFactory().uid
11
```

This recipe is most useful in a `TestCase`'s `setUp()` method.

Forcing the initial value for all projects The sequence counter of a `Factory` can also be set automatically upon the first call through the `_setup_next_sequence()` method; this helps when the objects's attributes mustn't conflict with pre-existing data.

A typical example is to ensure that running a Python script twice will create non-conflicting objects, by setting up the counter to "max used value plus one":

```
class AccountFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.Account

    @classmethod
    def _setup_next_sequence(cls):
        try:
            return models.Accounts.objects.latest('uid').uid + 1
        except models.Account.DoesNotExist:
            return 1
```

```
>>> Account.objects.create(uid=42, name="Blah")
>>> AccountFactory.create() # Sets up the account number based on the latest uid
<Account uid=43, name=Test>
```

7.4.8 Using reproducible randomness

Although using random values is great, it can provoke test flakyness. `factory_boy` provides a few helpers for this.

Note: Those methods will seed the random engine used in both `factory.Faker` and `factory.fuzzy` objects.

Seeding the random engine The simplest way to manage randomness is to push a selected seed when starting tests:

```
import factory.random
# Pass in any value
factory.random.reseed_random('my awesome project')
```

Reproducing unseeded tests A project might choose not to use an explicit random seed (for better fuzzing), but still wishes to have reproducible tests.

For such cases, use a combination of `factory.random.get_random_state()` and `factory.random.set_random_state()`.

Since the random state structure is implementation-specific, we recommend passing it around as a base64-encoded pickle dump.

```
class MyTestRunner:

    def setup_test_environment(self):
        state = os.environ.get('TEST_RANDOM_STATE')
        if state:
            try:
                decoded_state = pickle.loads(base64.b64decode(state.encode('ascii
↳')))
            except ValueError:
                decoded_state = None
        if decoded_state:
            factory.random.set_random_state(decoded_state)
        else:
            encoded_state = base64.b64encode(pickle.dumps(factory.random.get_
↳random_state()))
            print("Current random state: %s" % encoded_state.decode('ascii'))
        super().setup_test_environment()
```

7.4.9 Converting a factory's output to a dict

In order to inject some data to, say, a REST API, it can be useful to fetch the factory's data as a dict.

Internally, a factory will:

1. Merge declarations and overrides from all sources (class definition, call parameters, ...)
2. Resolve them into a dict
3. Pass that dict as keyword arguments to the model's `build/create` function

In order to get a dict, we'll just have to swap the model; the easiest way is to use `factory.build()`:

```
class UserFactory(factory.django.DjangoModelFactory):
    class Meta:
        model = models.User

    first_name = factory.Sequence(lambda n: "Agent %03d" % n)
    username = factory.Faker('user_name')
```

```
>>> factory.build(dict, FACTORY_CLASS=UserFactory)
{'first_name': 'Agent 001', 'username': 'john_doe'}
```

7.4.10 Fuzzifying Django model field choices

When defining a `FuzzyChoice` you can reuse the same choice list from the model field descriptor.

Use the `getter` kwarg to select the first element from each choice tuple.

```
class UserFactory(factory.Factory):
    class Meta:
        model = User

    # CATEGORY_CHOICES is a list of (key, title) tuples
    category = factory.fuzzy.FuzzyChoice(User.CATEGORY_CHOICES, getter=lambda c: c[0])
```

7.4.11 Django models with *GenericForeignKeys*

For model which uses `GenericForeignKey`

```

from __future__ import unicode_literals

from django.contrib.contenttypes.fields import GenericForeignKey
from django.contrib.contenttypes.models import ContentType
from django.db import models

class TaggedItem(models.Model):
    """Example GenericForeignKey model from django docs"""
    tag = models.SlugField()
    content_type = models.ForeignKey(ContentType, on_delete=models.CASCADE)
    object_id = models.PositiveIntegerField()
    content_object = GenericForeignKey('content_type', 'object_id')

    def __str__(self): # __unicode__ on Python 2
        return self.tag

```

We can create factories like this:

```

from django.contrib.auth.models import Group, User
from django.contrib.contenttypes.models import ContentType

import factory

from .models import TaggedItem

class UserFactory(factory.django.DjangoModelFactory):
    first_name = 'Adam'

    class Meta:
        model = User

class GroupFactory(factory.django.DjangoModelFactory):
    name = 'group'

    class Meta:
        model = Group

class TaggedItemFactory(factory.django.DjangoModelFactory):
    object_id = factory.SelfAttribute('content_object.id')
    content_type = factory.LazyAttribute(
        lambda o: ContentType.objects.get_for_model(o.content_object))

    class Meta:
        exclude = ['content_object']
        abstract = True

class TaggedUserFactory(TaggedItemFactory):
    content_object = factory.SubFactory(UserFactory)

```

(continues on next page)

(continued from previous page)

```
class Meta:
    model = TaggedItem

class TaggedGroupFactory(TaggedItemFactory):
    content_object = factory.SubFactory(GroupFactory)

class Meta:
    model = TaggedItem
```

7.5 Fuzzy attributes

Note: Now that FactoryBoy includes the `factory.Faker` class, most of these built-in fuzzers are deprecated in favor of their `Faker` equivalents. Further discussion here: https://github.com/FactoryBoy/factory_boy/issues/271/

Some tests may be interested in testing with fuzzy, random values.

This is handled by the `factory.fuzzy` module, which provides a few random declarations.

Note: Use `import factory.fuzzy` to load this module.

7.5.1 FuzzyAttribute

class `factory.fuzzy.FuzzyAttribute`

The `FuzzyAttribute` uses an arbitrary callable as fuzzer. It is expected that successive calls of that function return various values.

fuzzer

The callable that generates random values

7.5.2 FuzzyText

class `factory.fuzzy.FuzzyText` (`length=12`, `chars=string.ascii_letters`, `prefix=""`)

The `FuzzyText` fuzzer yields random strings beginning with the given `prefix`, followed by `length` characters chosen from the `chars` character set, and ending with the given `suffix`.

length

int, the length of the random part

prefix

text, an optional prefix to prepend to the random part

suffix

text, an optional suffix to append to the random part

chars

char iterable, the chars to choose from; defaults to the list of `ascii` letters and numbers.

7.5.3 FuzzyChoice

class `factory.fuzzy.FuzzyChoice` (*choices*)

The *FuzzyChoice* fuzzer yields random choices from the given iterable.

Note: The passed in *choices* will be converted into a list upon first use, not at declaration time.

This allows passing in, for instance, a Django queryset that will only hit the database during the database, not at import time.

Warning: When using Python2 and list comprehension, use private variable names as in:

```
[_x.name for _x in items]
```

instead of:

```
[x.name for x in items]
```

choices

The list of choices to select randomly

7.5.4 FuzzyInteger

class `factory.fuzzy.FuzzyInteger` (*low*[, *high*[, *step*]])

The *FuzzyInteger* fuzzer generates random integers within a given inclusive range.

The *low* bound may be omitted, in which case it defaults to 0:

```
>>> fi = FuzzyInteger(0, 42)
>>> fi.low, fi.high
0, 42

>>> fi = FuzzyInteger(42)
>>> fi.low, fi.high
0, 42
```

low

int, the inclusive lower bound of generated integers

high

int, the inclusive higher bound of generated integers

step

int, the step between values in the range; for instance, a `FuzzyInteger(0, 42, step=3)` might only yield values from `[0, 3, 6, 9, 12, 15, 18, 21, 24, 27, 30, 33, 36, 39, 42]`.

7.5.5 FuzzyDecimal

class `factory.fuzzy.FuzzyDecimal` (*low*[, *high*[, *precision=2*]])

The *FuzzyDecimal* fuzzer generates random *decimals* within a given inclusive range.

The *low* bound may be omitted, in which case it defaults to 0:

```
>>> FuzzyDecimal(0.5, 42.7)
>>> fi.low, fi.high
0.5, 42.7

>>> fi = FuzzyDecimal(42.7)
>>> fi.low, fi.high
0.0, 42.7

>>> fi = FuzzyDecimal(0.5, 42.7, 3)
>>> fi.low, fi.high, fi.precision
0.5, 42.7, 3
```

low

decimal, the inclusive lower bound of generated decimals

high

decimal, the inclusive higher bound of generated decimals

precision

int, the number of digits to generate after the dot. The default is 2 digits.

7.5.6 FuzzyFloat

class `factory.fuzzy.FuzzyFloat` (*low* [, *high*])

The *FuzzyFloat* fuzzer provides random `float` objects within a given inclusive range.

```
>>> FuzzyFloat(0.5, 42.7)
>>> fi.low, fi.high
0.5, 42.7

>>> fi = FuzzyFloat(42.7)
>>> fi.low, fi.high
0.0, 42.7
```

low

decimal, the inclusive lower bound of generated floats

high

decimal, the inclusive higher bound of generated floats

7.5.7 FuzzyDate

class `factory.fuzzy.FuzzyDate` (*start_date* [, *end_date*])

The *FuzzyDate* fuzzer generates random dates within a given inclusive range.

The *end_date* bound may be omitted, in which case it defaults to the current date:

```
>>> fd = FuzzyDate(datetime.date(2008, 1, 1))
>>> fd.start_date, fd.end_date
datetime.date(2008, 1, 1), datetime.date(2013, 4, 16)
```

start_date

`datetime.date`, the inclusive lower bound of generated dates

end_date

`datetime.date`, the inclusive higher bound of generated dates

7.5.8 FuzzyDateTime

```
class factory.fuzzy.FuzzyDateTime(start_dt[, end_dt], force_year=None, force_month=None,
                                   force_day=None, force_hour=None, force_minute=None,
                                   force_second=None, force_microsecond=None)
```

The `FuzzyDateTime` fuzzer generates random timezone-aware datetime within a given inclusive range.

The `end_dt` bound may be omitted, in which case it defaults to `datetime.datetime.now()` localized into the UTC timezone.

```
>>> fdt = FuzzyDateTime(datetime.datetime(2008, 1, 1, tzinfo=UTC))
>>> fdt.start_dt, fdt.end_dt
datetime.datetime(2008, 1, 1, tzinfo=UTC), datetime.datetime(2013, 4, 21, 19, 13,
↳32, 458487, tzinfo=UTC)
```

The `force_XXX` keyword arguments force the related value of generated datetimes:

```
>>> fdt = FuzzyDateTime(datetime.datetime(2008, 1, 1, tzinfo=UTC), datetime.
↳datetime(2009, 1, 1, tzinfo=UTC),
...     force_day=3, force_second=42)
>>> fdt.evaluate(2, None, False) # Actual code used by ``SomeFactory.build()``
datetime.datetime(2008, 5, 3, 12, 13, 42, 124848, tzinfo=UTC)
```

start_dt

`datetime.datetime`, the inclusive lower bound of generated datetimes

end_dt

`datetime.datetime`, the inclusive upper bound of generated datetimes

force_year

int or None; if set, forces the `year` of generated datetime.

force_month

int or None; if set, forces the `month` of generated datetime.

force_day

int or None; if set, forces the `day` of generated datetime.

force_hour

int or None; if set, forces the `hour` of generated datetime.

force_minute

int or None; if set, forces the `minute` of generated datetime.

force_second

int or None; if set, forces the `second` of generated datetime.

force_microsecond

int or None; if set, forces the `microsecond` of generated datetime.

7.5.9 FuzzyNaiveDateTime

```
class factory.fuzzy.FuzzyNaiveDateTime(start_dt[, end_dt], force_year=None,
                                        force_month=None, force_day=None,
                                        force_hour=None, force_minute=None,
                                        force_second=None, force_microsecond=None)
```

The `FuzzyNaiveDateTime` fuzzer generates random naive datetime within a given inclusive range.

The `end_dt` bound may be omitted, in which case it defaults to `datetime.datetime.now()`:

```
>>> fdt = FuzzyNaiveDateTime(datetime.datetime(2008, 1, 1))
>>> fdt.start_dt, fdt.end_dt
datetime.datetime(2008, 1, 1), datetime.datetime(2013, 4, 21, 19, 13, 32, 458487)
```

The `force_XXX` keyword arguments force the related value of generated datetimes:

```
>>> fdt = FuzzyNaiveDateTime(datetime.datetime(2008, 1, 1), datetime.
↳datetime(2009, 1, 1),
...     force_day=3, force_second=42)
>>> fdt.evaluate(2, None, False) # Actual code used by ``SomeFactory.build()``
datetime.datetime(2008, 5, 3, 12, 13, 42, 124848)
```

start_dt

`datetime.datetime`, the inclusive lower bound of generated datetimes

end_dt

`datetime.datetime`, the inclusive upper bound of generated datetimes

force_year

int or None; if set, forces the `year` of generated datetime.

force_month

int or None; if set, forces the `month` of generated datetime.

force_day

int or None; if set, forces the `day` of generated datetime.

force_hour

int or None; if set, forces the `hour` of generated datetime.

force_minute

int or None; if set, forces the `minute` of generated datetime.

force_second

int or None; if set, forces the `second` of generated datetime.

force_microsecond

int or None; if set, forces the `microsecond` of generated datetime.

7.5.10 Custom fuzzy fields

Alternate fuzzy fields may be defined. They should inherit from the `BaseFuzzyAttribute` class, and override its `fuzz()` method.

class `factory.fuzzy.BaseFuzzyAttribute`

Base class for all fuzzy attributes.

fuzz (*self*)

The method responsible for generating random values. *Must* be overridden in subclasses.

Warning: Custom `BaseFuzzyAttribute` subclasses **MUST** use `factory.random.randgen` as a randomness source; this ensures that data they generate can be regenerated using the simple state from `get_random_state()`.

7.6 Examples

Here are some real-world examples of using FactoryBoy.

7.6.1 Objects

First, let's define a couple of objects:

```
class Account(object):
    def __init__(self, username, email, date_joined):
        self.username = username
        self.email = email
        self.date_joined = date_joined

    def __str__(self):
        return '%s (%s)' % (self.username, self.email)

class Profile(object):

    GENDER_MALE = 'm'
    GENDER_FEMALE = 'f'
    GENDER_UNKNOWN = 'u' # If the user refused to give it

    def __init__(self, account, gender, firstname, lastname, planet='Earth'):
        self.account = account
        self.gender = gender
        self.firstname = firstname
        self.lastname = lastname
        self.planet = planet

    def __unicode__(self):
        return u'%s %s (%s)' % (
            unicode(self.firstname),
            unicode(self.lastname),
            unicode(self.account.username),
        )
```

7.6.2 Factories

And now, we'll define the related factories:

```
import datetime
import factory
import random

from . import objects

class AccountFactory(factory.Factory):
    class Meta:
        model = objects.Account

    username = factory.Sequence(lambda n: 'john%s' % n)
```

(continues on next page)

(continued from previous page)

```

email = factory.LazyAttribute(lambda o: '%s@example.org' % o.username)
date_joined = factory.LazyFunction(datetime.datetime.now)

class ProfileFactory(factory.Factory):
    class Meta:
        model = objects.Profile

    account = factory.SubFactory(AccountFactory)
    gender = factory.Iterator([objects.Profile.GENDER_MALE, objects.Profile.GENDER_
→FEMALE])
    firstname = u'John'
    lastname = u'Doe'

```

We have now defined basic factories for our `Account` and `Profile` classes.

If we commonly use a specific variant of our objects, we can refine a factory accordingly:

```

class FemaleProfileFactory(ProfileFactory):
    gender = objects.Profile.GENDER_FEMALE
    firstname = u'Jane'
    account__username = factory.Sequence(lambda n: 'jane%s' % n)

```

7.6.3 Using the factories

We can now use our factories, for tests:

```

import unittest

from . import business_logic
from . import factories
from . import objects

class MyTestCase(unittest.TestCase):

    def test_send_mail(self):
        account = factories.AccountFactory()
        email = business_logic.prepare_email(account, subject='Foo', text='Bar')

        self.assertEqual(email.to, account.email)

    def test_get_profile_stats(self):
        profiles = []

        profiles.extend(factories.ProfileFactory.create_batch(4))
        profiles.extend(factories.FemaleProfileFactory.create_batch(2))
        profiles.extend(factories.ProfileFactory.create_batch(2, planet="Tatooine"))

        stats = business_logic.profile_stats(profiles)
        self.assertEqual({'Earth': 6, 'Mars': 2}, stats.planets)
        self.assertLess(stats.genders[objects.Profile.GENDER_FEMALE], 2)

```

Or for fixtures:

```

from . import factories

def make_objects():
    factories.ProfileFactory.create_batch(size=50)

    # Let's create a few, known objects.
    factories.ProfileFactory(
        gender=objects.Profile.GENDER_MALE,
        firstname='Luke',
        lastname='Skywalker',
        planet='Tatooine',
    )

    factories.ProfileFactory(
        gender=objects.Profile.GENDER_FEMALE,
        firstname='Leia',
        lastname='Organa',
        planet='Alderaan',
    )

```

7.7 Internals

Behind the scenes: steps performed when parsing a factory declaration, and when calling it.

This section will be based on the following factory declaration:

```

class UserFactory(factory.Factory):
    class Meta:
        model = User

    class Params:
        # Allow us to quickly enable staff/superuser flags
        superuser = factory.Trait(
            is_superuser=True,
            is_staff=True,
        )
        # Meta parameter handling all 'enabled'-related fields
        enabled = True

    # Classic fields
    username = factory.Faker('user_name')
    full_name = factory.Faker('name')
    creation_date = factory.fuzzy.FuzzyDateTime(
        datetime.datetime(2000, 1, 1, tzinfo=UTC),
        datetime.datetime(2015, 12, 31, 20, tzinfo=UTC)
    )

    # Conditional flags
    is_active = factory.SelfAttribute('enabled')
    deactivation_date = factory.Maybe(
        'enabled',
        None,
        factory.fuzzy.FuzzyDateTime(
            datetime.datetime.now().replace(tzinfo=UTC) - datetime.timedelta(days=10),
            datetime.datetime.now().replace(tzinfo=UTC) - datetime.timedelta(days=1),
        )
    )

```

(continues on next page)

(continued from previous page)

```
    ),  
    )  
  
    # Related logs  
    creation_log = factory.RelatedFactory(  
        UserLogFactory, 'user',  
        action='create', timestamp=factory.SelfAttribute('user.creation_date'),  
    )
```

7.7.1 Parsing, Step 1: Metaclass and type declaration

1. Python parses the declaration and calls (thanks to the metaclass declaration):

```
factory.base.BaseFactory.__new__(  
    'UserFactory',  
    (factory.Factory,),  
    attributes,  
)
```

2. That metaclass removes *Meta* and *Params* from the class attributes, then generate the actual factory class (according to standard Python rules)
3. It initializes a *FactoryOptions* object, and links it to the class

7.7.2 Parsing, Step 2: adapting the class definition

1. The *FactoryOptions* reads the options from the *class Meta* declaration
2. It finds a few specific pointer (loading the model class, finding the reference factory for the sequence counter, etc.)
3. It copies declarations and parameters from parent classes
4. It scans current class attributes (from `vars()`) to detect pre/post declarations
5. Declarations are split among pre-declarations and post-declarations (a raw value shadowing a post-declaration is seen as a post-declaration)

Note: A declaration for `foo__bar` will be converted into parameter `bar` for declaration `foo`.

7.7.3 Instantiating, Step 1: Converging entrypoints

First, decide the strategy:

- If the endpoint is specific to a strategy (*build()*, *create_batch()*, ...), use it
- If it is generic (*generate()*, *Factory.__call__()*), use the strategy defined at the *class Meta* level

Then, we'll pass the strategy and passed-in overrides to the `_generate()` method.

Note: According to the project roadmap, a future version will use a `_generate_batch`()` at its core instead.

A factory's `_generate()` function actually delegates to a `StepBuilder()` object. This object will carry the overall “build an object” context (strategy, depth, and possibly other).

7.7.4 Instantiating, Step 2: Preparing values

1. The `StepBuilder` merges overrides with the class-level declarations
2. The sequence counter for this instance is initialized
3. A `Resolver` is set up with all those declarations, and parses them in order; it will call each value's `evaluate()` method, including extra parameters.
4. If needed, the `Resolver` might recurse (through the `StepBuilder`, e.g when encountering a `SubFactory`).

7.7.5 Instantiating, Step 3: Building the object

1. The `StepBuilder` fetches the attributes computed by the `Resolver`.
2. It applies renaming/adjustment rules
3. It passes them to the `FactoryOptions.instantiate()` method, which forwards to the proper methods.
4. Post-declaration are applied (in declaration order)

Note: This document discusses implementation details; there is no guarantee that the described methods names and signatures will be kept as is.

7.8 ChangeLog

7.8.1 2.12.1 (unreleased)

New:

- Add support for Python 3.8
- Add support for Django 2.2 and 3.0

Bugfix:

- Fix issue with `SubFactory` not preserving signal muting behaviour of the used factory, thanks [Patrick Stein](#).
- Fix issue with overriding params in a `Trait`, thanks [Grégoire Rocher](#).
- [issue #598](#): Limit `get_or_create` behavior to fields specified in `django_get_or_create`.
- [issue #606](#): Re-raise `IntegrityError` when `django_get_or_create` with multiple fields fails to lookup model using user provided keyword arguments.
- [issue #630](#): `TypeError` masked by `__repr__` `AttributeError` when initializing `Maybe` with inconsistent phases.

Removed:

- Drop support for Python 3.4. This version is **not maintained anymore**.
- Drop support for Django 2.0 and 2.1. These versions are **not maintained anymore**.

7.8.2 2.12.0 (2019-05-11)

New:

- Add support for Python 3.7
- Add support for Django 2.1
- Add `getter` to `FuzzyChoice` that mimics the behavior of `getter` in `Iterator`
- Make the `extra_kwargs` parameter of `generate()` optional
- Add `RelatedFactoryList` class for one-to-many support, thanks Sean Harrington.
- Make the `locale` argument for `Faker` keyword-only

Bugfix:

- Allow renamed arguments to be optional, thanks to Justin Crown.
- Fix `django_get_or_create` behavior when using multiple fields with `unique=True`, thanks to @YPCrumble <<https://github.com/YPCrumble>>

7.8.3 2.11.1 (2018-05-05)

Bugfix:

- Fix passing deep context to a `SubFactory` (`Foo(x__y__z=factory.Faker('name'))`)

7.8.4 2.11.0 (2018-05-05)

Bugfix:

- Fix `FuzzyFloat` to return a 15 decimal digits precision float by default
- [issue #451](#): Restore `FileField` to a `ParameterizedAttribute`, relying on composition to parse the provided parameters.
- [issue #389](#): Fix random state management with `faker`.
- [issue #466](#): Restore mixing `Trait` and `post_generation()`.

7.8.5 2.10.0 (2018-01-28)

Bugfix:

- [issue #443](#): Don't crash when calling `factory.Iterator.reset()` on a brand new iterator.

New:

- [issue #397](#): Allow a `factory.Maybe` to contain a `PostGenerationDeclaration`. This also applies to `factory.Trait`, since they use a `factory.Maybe` declaration internally.

7.8.6 2.9.2 (2017-08-03)

Bugfix:

- Fix declaration corruption bug when a factory defined `foo__bar__baz=1` and a caller provided a `foo__bar=x` parameter at call time: this got merged into the factory's base declarations.

7.8.7 2.9.1 (2017-08-02)

Bugfix:

- Fix packaging issues (see <https://github.com/zestsoftware/zest.releaser/issues/212>)
- Don't crash when debugging `PostGenerationDeclaration`

7.8.8 2.9.0 (2017-07-30)

This version brings massive changes to the core engine, thus reducing the number of corner cases and weird behaviours.

New:

- [issue #275](#): `factory.fuzzy` and `factory.faker` now use the same random seed.
- Add `factory.Maybe`, which chooses among two possible declarations based on another field's value (powers the `Trait` feature).
- `PostGenerationMethodCall` only allows to pass one positional argument; use keyword arguments for extra parameters.

Deprecation:

- `factory.fuzzy.get_random_state` is deprecated, `factory.random.get_random_state` should be used instead.
- `factory.fuzzy.set_random_state` is deprecated, `factory.random.set_random_state` should be used instead.
- `factory.fuzzy.reseed_random` is deprecated, `factory.random.reseed_random` should be used instead.

7.8.9 2.8.1 (2016-12-17)

Bugfix:

- Fix packaging issues.

7.8.10 2.8.0 (2016-12-17)

New:

- [issue #240](#): Call post-generation declarations in the order they were declared, thanks to Oleg Pidsadnyi.
- [issue #309](#): Provide new options for SQLAlchemy session persistence

Bugfix:

- [issue #334](#): Adjust for the package change in `faker`

7.8.11 2.7.0 (2016-04-19)

New:

- [pull request #267](#): Add `factory.LazyFunction` to remove unneeded lambda parameters, thanks to Hervé Cauwelier.
- [issue #251](#): Add `parameterized factories` and `traits`
- [pull request #256](#), [pull request #292](#): Improve error messages in corner cases

Removed:

- [pull request #278](#): Formally drop support for Python2.6

Warning: Version 2.7.0 moves all error classes to *factory.errors*. This breaks existing import statements for any error classes except those importing *FactoryError* directly from the *factory* module.

7.8.12 2.6.1 (2016-02-10)

New:

- [pull request #262](#): Allow optional forced flush on SQLAlchemy, courtesy of [Minjung](#).

7.8.13 2.6.0 (2015-10-20)

New:

- Add *factory.FactoryOptions.rename* to help handle conflicting names ([issue #206](#))
- Add support for random-yet-realistic values through *fake-factory*, through the *factory.Faker* class.
- *factory.Iterator* no longer begins iteration of its argument at import time, thus allowing to pass in a lazy iterator such as a Django queryset (i.e `factory.Iterator(models.MyThingy.objects.all())`).
- Simplify imports for ORM layers, now available through a simple *factory* import, at `factory.alchemy.SQLAlchemyModelFactory / factory.django.DjangoModelFactory / factory.mongoengine.MongoEngineFactory`.

Bugfix:

- [issue #201](#): Properly handle custom Django managers when dealing with abstract Django models.
- [issue #212](#): Fix *factory.django.mute_signals()* to handle Django's signal caching
- [issue #228](#): Don't load `django.apps.apps.get_model()` until required
- [pull request #219](#): Stop using `mogo.model.Model.new()`, deprecated 4 years ago.

7.8.14 2.5.2 (2015-04-21)

Bugfix:

- Add support for Django 1.7/1.8
- Add support for `mongoengine>=0.9.0 / pymongo>=2.1`

7.8.15 2.5.1 (2015-03-27)

Bugfix:

- Respect custom managers in *DjangoModelFactory* (see [issue #192](#))
- Allow passing declarations (e.g *Sequence*) as parameters to *FileField* and *ImageField*.

7.8.16 2.5.0 (2015-03-26)

New:

- Add support for getting/setting `factory.fuzzy`'s random state (see issue #175, issue #185).
- Support lazy evaluation of iterables in `factory.fuzzy.FuzzyChoice` (see issue #184).
- Support non-default databases at the factory level (see issue #171)
- Make `factory.django.FileField` and `factory.django.ImageField` non-post_generation, i.e normal fields also available in `save()` (see issue #141).

Bugfix:

- Avoid issues when using `factory.django.mute_signals()` on a base factory class (see issue #183).
- Fix limitations of `factory.StubFactory`, that can now use `factory.SubFactory` and `co` (see issue #131).

Deprecation:

- Remove deprecated features from 2.4.0 (2014-06-21)
- Remove the auto-magical sequence setup (based on the latest primary key value in the database) for Django and SQLAlchemy; this relates to issues issue #170, issue #153, issue #111, issue #103, issue #92, issue #78. See https://github.com/FactoryBoy/factory_boy/commit/13d310f for technical details.

Warning: Version 2.5.0 removes the 'auto-magical sequence setup' bug-and-feature. This could trigger some bugs when tests expected a non-zero sequence reference.

Upgrading

Warning: Version 2.5.0 removes features that were marked as deprecated in v2.4.0.

All `FACTORY_*`-style attributes are now declared in a `class Meta:` section:

```
# Old-style, deprecated
class MyFactory(factory.Factory):
    FACTORY_FOR = models.MyModel
    FACTORY_HIDDEN_ARGS = ['a', 'b', 'c']

# New-style
class MyFactory(factory.Factory):
    class Meta:
        model = models.MyModel
        exclude = ['a', 'b', 'c']
```

A simple shell command to upgrade the code would be:

```
# sed -i: inplace update
# grep -l: only file names, not matching lines
sed -i 's/FACTORY_FOR =/class Meta:\n        model =/' $(grep -l FACTORY_FOR $(find . -\
↪-name '*.py'))
```

This takes care of all `FACTORY_FOR` occurrences; the files containing other attributes to rename can be found with `grep -R FACTORY .`

7.8.17 2.4.1 (2014-06-23)

Bugfix:

- Fix overriding deeply inherited attributes (set in one factory, overridden in a subclass, used in a sub-sub-class).

7.8.18 2.4.0 (2014-06-21)

New:

- Add support for `factory.fuzzy.FuzzyInteger.step`, thanks to ilya-pirogov (pull request #120)
- Add `mute_signals()` decorator to temporarily disable some signals, thanks to ilya-pirogov (pull request #122)
- Add `FuzzyFloat` (issue #124)
- Declare target model and other non-declaration fields in a `class Meta` section.

Deprecation:

- Use of `FACTORY_FOR` and other `FACTORY` class-level attributes is deprecated and will be removed in 2.5. Those attributes should now be declared within the `class Meta` attribute:

For `factory.Factory`:

- Rename `FACTORY_FOR` to `model`
- Rename `ABSTRACT_FACTORY` to `abstract`
- Rename `FACTORY_STRATEGY` to `strategy`
- Rename `FACTORY_ARG_PARAMETERS` to `inline_args`
- Rename `FACTORY_HIDDEN_ARGS` to `exclude`

For `factory.django.DjangoModelFactory`:

- Rename `FACTORY_DJANGO_GET_OR_CREATE` to `django_get_or_create`

For `factory.alchemy.SQLAlchemyModelFactory`:

- Rename `FACTORY_SESSION` to `sqlalchemy_session`

7.8.19 2.3.1 (2014-01-22)

Bugfix:

- Fix badly written assert containing state-changing code, spotted by chsigi (pull request #126)
- Don't crash when handling objects whose `__repr__` is non-pure-ascii bytes on Py2, discovered by mbertheau (issue #123) and strycore (pull request #127)

7.8.20 2.3.0 (2013-12-25)

New:

- Add `FuzzyText`, thanks to jdufresne (pull request #97)
- Add `FuzzyDecimal`, thanks to thedraw (pull request #94)
- Add support for `EmbeddedDocument`, thanks to imiric (pull request #100)

7.8.21 2.2.1 (2013-09-24)

Bugfix:

- Fixed sequence counter for *DjangoModelFactory* when a factory inherits from another factory relating to an abstract model.

7.8.22 2.2.0 (2013-09-24)

Bugfix:

- Removed duplicated *SQLAlchemyModelFactory* lurking in *factory* (pull request #83)
- Properly handle sequences within object inheritance chains. If *FactoryA* inherits from *FactoryB*, and their associated classes share the same link, sequence counters will be shared (issue #93)
- Properly handle nested *SubFactory* overrides

New:

- The *DjangoModelFactory* now supports the `FACTORY_FOR = 'myapp.MyModel'` syntax, making it easier to shove all factories in a single module (issue #66).
- Add *factory.debug()* helper for easier backtrace analysis
- Adding factory support for mongoengine with *MongoEngineFactory*.

7.8.23 2.1.2 (2013-08-14)

New:

- The `ABSTRACT_FACTORY` keyword is now optional, and automatically set to `True` if neither the *Factory* subclass nor its parent declare the `FACTORY_FOR` attribute (issue #74)

7.8.24 2.1.1 (2013-07-02)

Bugfix:

- Properly retrieve the `color` keyword argument passed to *ImageField*

7.8.25 2.1.0 (2013-06-26)

New:

- Add *FuzzyDate* thanks to saulshanabrook
- Add *FuzzyDateTime* and *FuzzyNaiveDateTime*.
- Add a `factory_parent` attribute to the Resolver passed to *LazyAttribute*, in order to access fields defined in wrapping factories.
- Move *DjangoModelFactory* and *MogoFactory* to their own modules (`factory.django` and `factory.mogo`)
- Add the *reset_sequence()* classmethod to *Factory* to ease resetting the sequence counter for a given factory.
- Add debug messages to *factory* logger.

- Add a `reset()` method to `Iterator` (issue #63)
- Add support for the SQLAlchemy ORM through `SQLAlchemyModelFactory` (pull request #64, thanks to Romain Commandé)
- Add `factory.django.FileField` and `factory.django.ImageField` hooks for related Django model fields (issue #52)

Bugfix

- Properly handle non-integer pks in `DjangoModelFactory` (issue #57).
- Disable `RelatedFactory` generation when a specific value was passed (issue #62, thanks to Gabe Koscky)

Deprecation:

- Rename `RelatedFactory`'s `name` argument to `factory_related_name` (See issue #58)

7.8.26 2.0.2 (2013-04-16)

New:

- When `FACTORY_DJANGO_GET_OR_CREATE` is empty, use `Model.objects.create()` instead of `Model.objects.get_or_create`.

7.8.27 2.0.1 (2013-04-16)

New:

- Don't push defaults to `get_or_create` when `FACTORY_DJANGO_GET_OR_CREATE` is not set.

7.8.28 2.0.0 (2013-04-15)

New:

- Allow overriding the base factory class for `make_factory()` and friends.
- Add support for Python3 (Thanks to kmike and nkryptic)
- The default type for `Sequence` is now `int`
- Fields listed in `FACTORY_HIDDEN_ARGS` won't be passed to the associated class' constructor
- Add support for `get_or_create` in `DjangoModelFactory`, through `FACTORY_DJANGO_GET_OR_CREATE`.
- Add support for `fuzzy` attribute definitions.
- The `Sequence` counter can be overridden when calling a generating function
- Add `Dict` and `List` declarations (Closes issue #18).

Removed:

- Remove associated class discovery
- Remove `InfiniteIterator` and `infinite_iterator()`
- Remove `CircularSubFactory`
- Remove `extract_prefix` kwarg to post-generation hooks.
- Stop defaulting to Django's `Foo.objects.create()` when "creating" instances

- Remove `STRATEGY_*`
- Remove `set_building_function()` / `set_creation_function()`

7.8.29 1.3.0 (2013-03-11)

Warning: This version deprecates many magic or unexplicit features that will be removed in v2.0.0. Please read the *Upgrading* section, then run your tests with `python -W default` to see all remaining warnings.

New

- **Global:**
 - Rewrite the whole documentation
 - Provide a dedicated *MogoFactory* subclass of *Factory*
- **The Factory class:**
 - Better creation/building customization hooks at *factory.Factory._build()* and *factory.Factory.create()*
 - Add support for passing non-kwarg parameters to a *Factory* wrapped class through `FACTORY_ARG_PARAMETERS`.
 - Keep the `FACTORY_FOR` attribute in *Factory* classes
- **Declarations:**
 - Allow *SubFactory* to solve circular dependencies between factories
 - Enhance *SelfAttribute* to handle “container” attribute fetching
 - Add a *getter* to *Iterator* declarations
 - A *Iterator* may be prevented from cycling by setting its *cycle* argument to `False`
 - Allow overriding default arguments in a *PostGenerationMethodCall* when generating an instance of the factory
 - An object created by a *DjangoModelFactory* will be saved again after *PostGeneration* hooks execution

Pending deprecation

The following features have been deprecated and will be removed in an upcoming release.

- **Declarations:**
 - *InfiniteIterator* is deprecated in favor of *Iterator*
 - *CircularSubFactory* is deprecated in favor of *SubFactory*
 - The `extract_prefix` argument to *post_generation()* is now deprecated
- **Factory:**
 - Usage of `set_creation_function()` and `set_building_function()` are now deprecated

- Implicit associated class discovery is no longer supported, you must set the `FACTORY_FOR` attribute on all *Factory* subclasses

Upgrading

This version deprecates a few magic or undocumented features. All warnings will turn into errors starting from v2.0.0.

In order to upgrade client code, apply the following rules:

- Add a `FACTORY_FOR` attribute pointing to the target class to each *Factory*, instead of relying on automagic associated class discovery
- When using `factory_boy` for Django models, have each factory inherit from *DjangoModelFactory*
- Replace `factory.CircularSubFactory('some.module', 'Symbol')` with `factory.SubFactory('some.module.Symbol')`
- Replace `factory.InfiniteIterator(iterable)` with `factory.Iterator(iterable)`
- Replace `@factory.post_generation()` with `@factory.post_generation`
- Replace `factory.set_building_function(SomeFactory, building_function)` with an override of the `_build()` method of *SomeFactory*
- Replace `factory.set_creation_function(SomeFactory, creation_function)` with an override of the `_create()` method of *SomeFactory*

7.8.30 1.2.0 (2012-09-08)

New:

- Add *CircularSubFactory* to solve circular dependencies between factories

7.8.31 1.1.5 (2012-07-09)

Bugfix:

- Fix *PostGenerationDeclaration* and derived classes.

7.8.32 1.1.4 (2012-06-19)

New:

- Add `use_strategy()` decorator to override a *Factory*'s default strategy
- Improve test running (tox, python2.6/2.7)
- Introduce *PostGeneration* and *RelatedFactory*

7.8.33 1.1.3 (2012-03-09)

Bugfix:

- Fix packaging rules

7.8.34 1.1.2 (2012-02-25)

New:

- Add *Iterator* and *InfiniteIterator* for *Factory* attribute declarations.
- Provide *generate()* and *simple_generate()*, that allow specifying the instantiation strategy directly. Also provides *generate_batch()* and *simple_generate_batch()*.

7.8.35 1.1.1 (2012-02-24)

New:

- Add *build_batch()*, *create_batch()* and *stub_batch()*, to instantiate factories in batch

7.8.36 1.1.0 (2012-02-24)

New:

- Improve the *SelfAttribute* syntax to fetch sub-attributes using the `foo.bar` syntax;
- Add *ContainerAttribute* to fetch attributes from the container of a *SubFactory*.
- Provide the *make_factory()* helper: `MyClassFactory = make_factory(MyClass, x=3, y=4)`
- Add *build()*, *create()*, *stub()* helpers

Bugfix:

- Allow `classmethod/staticmethod` on factories

Deprecation:

- Auto-discovery of `FACTORY_FOR` based on class name is now deprecated

7.8.37 1.0.4 (2011-12-21)

New:

- Improve the algorithm for populating a *Factory* attributes dict
- Add `python setup.py test` command to run the test suite
- Allow custom build functions
- Introduce `MOGO_BUILD` build function
- Add support for inheriting from multiple *Factory*
- Base *Factory* classes can now be declared abstract.
- Provide *DjangoModelFactory*, whose *Sequence* counter starts at the next free database id
- Introduce *SelfAttribute*, a shortcut for `factory.LazyAttribute(lambda o: o.foo.bar.baz)`.

Bugfix:

- Handle nested *SubFactory*
- Share sequence counter between parent and subclasses

- Fix *SubFactory* / *Sequence* interferences

7.8.38 1.0.2 (2011-05-16)

New:

- Introduce *SubFactory*

7.8.39 1.0.1 (2011-05-13)

New:

- Allow *Factory* inheritance
- Improve handling of custom build/create functions

Bugfix:

- Fix concurrency between *LazyAttribute* and *Sequence*

7.8.40 1.0.0 (2010-08-22)

New:

- First version of `factory_boy`

7.8.41 Credits

- Initial version by Mark Sandstrom (2010)
- Developed by Raphaël Barrois since 2011

7.9 Credits

7.9.1 Maintainers

The `factory_boy` project is operated and maintained by:

- Jeff Widman <jeff@jeffwidman.com> (<https://github.com/jeffwidman>)
- Raphaël Barrois <raphael.barrois+fboy@polytechnique.org> (<https://github.com/rbarrois>)

7.9.2 Contributors

The project was initially created by Mark Sandstrom <mark@deliciouslynerdy.com>.

The project has received contributions from (in alphabetical order):

- Adam Chainz <adam@adamj.eu>
- Alejandro <tovarich@gmail.com>
- Alexey Kotlyarov <a@koterpillar.com>
- Amit Shah <amit@amwam.me>

- Anas Zahim <zanass0@gmail.com> (<https://github.com/kamotos>)
- Andrey Voronov <voronov84@gmail.com>
- Branko Majic <branko@majic.rs>
- Carl Meyer <carl@oddbird.net>
- Chris Lasher <chris.lasher@gmail.com>
- Chris Seto <chriskseto@gmail.com>
- Christoph Sieghart <sigi@0x2a.at>
- David Baumgold <david@davidbaumgold.com>
- Demur Nodia <demur.nodia@gmail.com> (<https://github.com/demonno>)
- Eduard Iskandarov <edikexp@gmail.com>
- Federico Bond <federicobond@gmail.com> (<https://github.com/federicobond>)
- Flavio Curella <flavio.curella@gmail.com>
- François Freitag <mail@franak.fr>
- George Hickman <george@ghickman.co.uk>
- Hervé Cauwelier <herve.cauwelier@polyconseil.fr>
- Hugo Osvaldo Barrera <hugo@barrera.io>
- Ilya Baryshev <baryshev@gmail.com>
- Ilya Pirogov <ilja.pirogov@gmail.com>
- Ionuț Artăriși <ionut@artarisi.eu>
- Issa Jubril <issa.jubril@andela.com>
- Ivan Miric <imiric@gmail.com>
- Janusz Skonieczny <wooyek@users.noreply.github.com>
- Jeff Widman <jeff@jeffwidman.com> (<https://github.com/jeffwidman>)
- Jon Dufresne <jon.dufresne@gmail.com>
- Jonathan Tushman <jtushman@pipewave.com>
- Joshua Carp <jm.carp@gmail.com>
- Leonardo Lazzaro <llazzaro@dc.uba.ar>
- Luke GB <github@lukegb.com>
- Marc Abramowitz <marc@marc-abramowitz.com>
- Mark Sandstrom <mark@deliciouslynerdy.com>
- Martin Bächtold <martin+factoryboy@baechtold.me> (<https://github.com/mbaechtold>)
- Michael Joseph <michaeljoseph+github@gmail.com>
- Mikhail Korobov <kmike84@gmail.com>
- Oleg Pidsadnyi <oleg.pidsadnyi@gmail.com>
- Omer <omer@stokeet.com>
- Pauly Fenwar <fenney@gmail.com>

- Peter Marsh <pete@skimlinks.com>
- Puneeth Chaganti <punchagan@muse-amuse.in>
- QuantumGhost <obelisk.reg+github@gmail.com>
- Raphaël Barrois <raphael.barrois+fboy@polytechnique.org> (<https://github.com/rbarrois>)
- Rich Rauenzahn <rich@vmware.com>
- Richard Moch <richard@mbp.polyconseil.fr>
- Rob Zyskowski <zyskowski.rob@gmail.com>
- Robrecht De Rouck <Robrecht.De.Rouck@gmail.com>
- Samuel Paccoud <samuel@sampaccoud.com>
- Saul Shanabrook <s.shanabrook@gmail.com>
- Sean Löfgren <SeanBE@users.noreply.github.com>
- Tom <tom@tomleo.com>
- alex-netquity <alex@netquity.com>
- anentropic <ego@anentropic.com>
- minimumserious <commande.romain@gmail.com>
- mluszczczyk <mluszczczyk@users.noreply.github.com>
- nkryptic <nkryptic@gmail.com>
- obiwanus <ivan@ivanovs.info>
- tsouvarev <tsouvarev@mail.ru>
- yamaneko <yamaneko1212@gmail.com>

7.9.3 Contributor license agreement

Note: This agreement is required to allow redistribution of submitted contributions. See <http://oss-watch.ac.uk/resources/cla> for an explanation.

Any contributor proposing updates to the code or documentation of this project *MUST* add its name to the list in the *Contributors* section, thereby “signing” the following contributor license agreement:

They accept and agree to the following terms for their present and future contributions submitted to the `factory_boy` project:

- They represent that they are legally entitled to grant this license, and that their contributions are their original creation
- They grant the `factory_boy` project a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare derivative works of, publicly display, sublicense and distribute their contributions and such derivative works.
- They are not expected to provide support for their contributions, except to the extent they desire to provide support.

Note: The above agreement is inspired by the Apache Contributor License Agreement.

7.10 Ideas

This is a list of future features that may be incorporated into factory_boy:

- When a `Factory` is built or created, pass the calling context throughout the calling chain instead of custom solutions everywhere
- Define a proper set of rules for the support of third-party ORMs
- Properly evaluate nested declarations (e.g `factory.fuzzy.FuzzyDate(start_date=factory.SelfAttribute('since'))`)
- `genindex`
- `modindex`
- `search`

f

`factory.fuzzy`, 68

Symbols

[__init__\(\)](#) (*factory.django.FileField method*), 52
[__init__\(\)](#) (*factory.django.ImageField method*), 53
[_adjust_kwargs\(\)](#) (*factory.Factory class method*), 25
[_after_postgeneration\(\)](#) (*factory.Factory class method*), 26
[_build\(\)](#) (*factory.Factory class method*), 26
[_create\(\)](#) (*factory.Factory class method*), 26
[_meta](#) (*factory.Factory attribute*), 24
[_options_class](#) (*factory.Factory attribute*), 25
[_setup_next_sequence\(\)](#) (*factory.Factory class method*), 26

A

[abstract](#) (*factory.FactoryOptions attribute*), 23
[add_provider\(\)](#) (*factory.Faker class method*), 31
[arg](#) (*factory.PostGenerationMethodCall attribute*), 47

B

[BaseFuzzyAttribute](#) (*class in factory.fuzzy*), 72
[build\(\)](#) (*factory.Factory class method*), 25
[build\(\)](#) (*in module factory*), 49
[build_batch\(\)](#) (*factory.Factory class method*), 25
[build_batch\(\)](#) (*in module factory*), 50
[BUILD_STRATEGY](#) (*in module factory*), 29

C

[chars](#) (*factory.fuzzy.FuzzyText attribute*), 68
[choices](#) (*factory.fuzzy.FuzzyChoice attribute*), 69
[create\(\)](#) (*factory.Factory class method*), 25
[create\(\)](#) (*in module factory*), 50
[create_batch\(\)](#) (*factory.Factory class method*), 25
[create_batch\(\)](#) (*in module factory*), 50
[CREATE_STRATEGY](#) (*in module factory*), 29
[cycle](#) (*factory.Iterator attribute*), 40

D

[database](#) (*factory.django.DjangoOptions attribute*), 52

[debug\(\)](#) (*in module factory*), 30
[Dict](#) (*class in factory*), 42
[dict_factory](#) (*factory.Dict attribute*), 42
[django_get_or_create](#) (*factory.django.DjangoOptions attribute*), 52
[DjangoModelFactory](#) (*class in factory.django*), 51
[DjangoOptions](#) (*class in factory.django*), 52

E

[end_date](#) (*factory.fuzzy.FuzzyDate attribute*), 70
[end_dt](#) (*factory.fuzzy.FuzzyDateTime attribute*), 71
[end_dt](#) (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
[exclude](#) (*factory.FactoryOptions attribute*), 23

F

[Factory](#) (*class in factory*), 24
[factory](#) (*factory.RelatedFactory attribute*), 44
[factory](#) (*factory.RelatedFactoryList attribute*), 45
[factory.fuzzy](#) (*module*), 68
[FactoryOptions](#) (*class in factory*), 23
[Faker](#) (*class in factory*), 31
[FileField](#) (*class in factory.django*), 52
[force_day](#) (*factory.fuzzy.FuzzyDateTime attribute*), 71
[force_day](#) (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
[force_flush](#) (*factory.alchemy.SQLAlchemyOptions attribute*), 56
[force_hour](#) (*factory.fuzzy.FuzzyDateTime attribute*), 71
[force_hour](#) (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
[force_microsecond](#) (*factory.fuzzy.FuzzyDateTime attribute*), 71
[force_microsecond](#) (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
[force_minute](#) (*factory.fuzzy.FuzzyDateTime attribute*), 71

force_minute (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
 force_month (*factory.fuzzy.FuzzyDateTime attribute*), 71
 force_month (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
 force_second (*factory.fuzzy.FuzzyDateTime attribute*), 71
 force_second (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
 force_year (*factory.fuzzy.FuzzyDateTime attribute*), 71
 force_year (*factory.fuzzy.FuzzyNaiveDateTime attribute*), 72
 fuzz () (*factory.fuzzy.BaseFuzzyAttribute method*), 72
 fuzzer (*factory.fuzzy.FuzzyAttribute attribute*), 68
 FuzzyAttribute (*class in factory.fuzzy*), 68
 FuzzyChoice (*class in factory.fuzzy*), 69
 FuzzyDate (*class in factory.fuzzy*), 70
 FuzzyDateTime (*class in factory.fuzzy*), 71
 FuzzyDecimal (*class in factory.fuzzy*), 69
 FuzzyFloat (*class in factory.fuzzy*), 70
 FuzzyInteger (*class in factory.fuzzy*), 69
 FuzzyNaiveDateTime (*class in factory.fuzzy*), 71
 FuzzyText (*class in factory.fuzzy*), 68

G

generate () (*factory.Factory class method*), 25
 generate () (*in module factory*), 50
 generate_batch () (*factory.Factory class method*), 25
 generate_batch () (*in module factory*), 50
 get_model_class () (*factory.FactoryOptions method*), 23
 get_random_state () (*in module factory.random*), 51
 getter (*factory.Iterator attribute*), 40

H

high (*factory.fuzzy.FuzzyDecimal attribute*), 70
 high (*factory.fuzzy.FuzzyFloat attribute*), 70
 high (*factory.fuzzy.FuzzyInteger attribute*), 69

I

ImageField (*class in factory.django*), 53
 inline_args (*factory.FactoryOptions attribute*), 23
 Iterator (*class in factory*), 40
 iterator () (*in module factory*), 41

K

kwargs (*factory.PostGenerationMethodCall attribute*), 47

L

lazy_attribute () (*in module factory*), 33
 lazy_attribute_sequence () (*in module factory*), 36
 LazyAttribute (*class in factory*), 32
 LazyAttributeSequence (*class in factory*), 35
 LazyFunction (*class in factory*), 32
 length (*factory.fuzzy.FuzzyText attribute*), 68
 List (*class in factory*), 42
 list_factory (*factory.List attribute*), 42
 locale (*factory.Faker attribute*), 31
 low (*factory.fuzzy.FuzzyDecimal attribute*), 70
 low (*factory.fuzzy.FuzzyFloat attribute*), 70
 low (*factory.fuzzy.FuzzyInteger attribute*), 69

M

make_factory () (*in module factory*), 49
 Maybe (*class in factory*), 43
 Meta (*factory.Factory attribute*), 24
 method_name (*factory.PostGenerationMethodCall attribute*), 47
 model (*factory.FactoryOptions attribute*), 23
 MogoFactory (*class in factory.mogo*), 54
 MongoEngineFactory (*class in factory.mongoengine*), 54
 mute_signals () (*in module factory.django*), 54

N

name (*factory.RelatedFactory attribute*), 44
 name (*factory.RelatedFactoryList attribute*), 46

O

override_default_locale () (*factory.Faker class method*), 31

P

Params (*factory.Factory attribute*), 24
 post_generation () (*in module factory*), 47
 PostGeneration (*class in factory*), 46
 PostGenerationMethodCall (*class in factory*), 47
 precision (*factory.fuzzy.FuzzyDecimal attribute*), 70
 prefix (*factory.fuzzy.FuzzyText attribute*), 68

R

RelatedFactory (*class in factory*), 44
 RelatedFactoryList (*class in factory*), 45
 rename (*factory.FactoryOptions attribute*), 24
 reseed_random () (*in module factory.random*), 51
 reset () (*factory.Iterator method*), 40
 reset_sequence () (*factory.Factory class method*), 26

S

SelfAttribute (*class in factory*), 39

Sequence (*class in factory*), 33
 sequence () (*in module factory*), 34
 set_random_state () (*in module factory.random*),
 51
 simple_generate () (*factory.Factory class method*),
 25
 simple_generate () (*in module factory*), 50
 simple_generate_batch () (*factory.Factory class
 method*), 25
 simple_generate_batch () (*in module factory*),
 50
 size (*factory.RelatedFactoryList attribute*), 46
 sqlalchemy_session (*factory.alchemy.SQLAlchemyOptions
 attribute*),
 55
 sqlalchemy_session_persistence (*factory.alchemy.SQLAlchemyOptions
 attribute*),
 56
 SQLAlchemyModelFactory (*class in fac-
 tory.alchemy*), 55
 SQLAlchemyOptions (*class in factory.alchemy*), 55
 start_date (*factory.fuzzy.FuzzyDate attribute*), 70
 start_dt (*factory.fuzzy.FuzzyDateTime attribute*), 71
 start_dt (*factory.fuzzy.FuzzyNaiveDateTime at-
 tribute*), 72
 step (*factory.fuzzy.FuzzyInteger attribute*), 69
 strategy (*factory.FactoryOptions attribute*), 24
 stub () (*factory.Factory class method*), 25
 stub () (*in module factory*), 50
 stub_batch () (*factory.Factory class method*), 25
 stub_batch () (*in module factory*), 50
 STUB_STRATEGY (*in module factory*), 30
 StubFactory (*class in factory*), 30
 StubObject (*class in factory*), 30
 SubFactory (*class in factory*), 36
 suffix (*factory.fuzzy.FuzzyText attribute*), 68

T

Trait (*class in factory*), 28

U

use_strategy () (*in module factory*), 30